

The `scripture` package

David Purton*

2023/01/08 v1.3

Abstract

The `scripture` package provides a set of macros for typesetting quotations from the Bible. It provides many features commonly seen in Bibles such as dropped text for chapter numbers, superscripts for verse numbers, indented lines for poetry sections, narrow sections and hanging paragraphs. A reference for the quotation can optionally be added.

Contents

1	Introduction	2
1.1	Bug reports and feature requests	2
1.2	Limitations	2
2	Documentation	3
2.1	Basic usage	3
2.2	Macros for typesetting scripture quotations	3
2.2.1	Functions	3
2.2.2	Environments	7
2.3	Provided hooks	11
2.4	Options	12
2.4.1	Options for the <code>center</code> environment	19
2.4.2	Options for the <code>flushright</code> environment	20
2.4.3	Options for the <code>hanging</code> environment	20
2.4.4	Options for the <code>midparachap</code> environment	21
2.4.5	Options for the <code>narrow</code> environment	21
2.4.6	Options for the <code>poetry</code> environment	22

*Email: dcpurton@marshwiggle.net

3	Implementation	23
3.1	Messages	23
3.2	Options	24
3.3	Hooks	29
3.4	The main <code>scripture</code> environment	29
3.4.1	Formatting and printing quotation references	30
3.4.2	Red lettering	32
3.4.3	Selecting language	32
3.4.4	Formatting and printing chapter numbers	33
3.4.5	Formatting and printing verse numbers	36
3.4.6	Calculating the length of the final line in a paragraph	37
3.4.7	The <code>scripture</code> environment	38
3.5	Scripture internal environments	43
3.5.1	The <code>center</code> environment	43
3.5.2	The <code>flushright</code> environment	44
3.5.3	The <code>hanging</code> environment	45
3.5.4	The <code>midparachap</code> environment	49
3.5.5	The <code>narrow</code> environment	53
3.5.6	The <code>poetry</code> environment	54
3.6	Public L ^A T _E X Interface	62
Change History		65
Index		65

1 Introduction

Bibles tend to use a number of standard features when laying out chapters and verses. The main goal for the `scripture` package is to be able to quickly and easily input text and have it output nicely with minimal manual adjustment.

The package supports dropped text for chapter numbers, superscripts for verse numbers, appropriately indented lines for the first and second halves of poetry, flush right sections, centred sections, narrow sections and hanging sections.

The package could be used for typesetting an entire Bible, but it is mainly envisioned that it will be used for producing Scripture quotations. The passage reference can be included on the last line if there is space or failing that on the following line.

1.1 Bug reports and feature requests

Bug reports and feature requests can be made at the `scripture` package GitHub repository. See <https://github.com/dcpurton/scripture>.

1.2 Limitations

The scripture package makes extensive use of L^AT_EX list environments and the \parshape command. This means there are some limitations. In particular, you should not:

- Nest the `scripture` environment or any of its internal environments.
- Modify the `\parshape` within a `scripture` environment.
- Include any other `list` based environment within a `scripture` environment.

The `poetry` environment uses `\obeylines`. This means that it can not be placed in the argument of a macro.

Some attempt is made to encourage appropriate page breaks, especially just before a reference is added to a quotation, but this can still sometimes fail and a reference will end up on the following page. Usually a little more stretchable space on the page before the incorrect break is enough to obtain acceptable output.

At least version 2022-06-01 of the L^AT_EX format is required.

2 Documentation

2.1 Basic usage

Scripture quotations must be set within a `scripture` environment. A simple quotation might be produced as follows:

```
\begin{scripture}[Isaiah 56:1--2][version=NIVUK]
\ch{56}This is what the \name{Lord} says:
\begin{poetry}
‘Maintain justice
and do what is right,
for my salvation is close at hand
and my righteousness will soon
be revealed.
\vs{2}Blessed is the one who does this---
the person who holds it fast,
who keeps the Sabbath without desecrating it,
and keeps their hands from doing any evil.’
\end{poetry}
\end{scripture}
```

56 This is what the LORD says:
‘Maintain justice
and do what is right,
for my salvation is close at hand
and my righteousness will soon
be revealed.
²Blessed is the one who does this—
the person who holds it fast,
who keeps the Sabbath without
desecrating it,
and keeps their hands from
doing any evil.’
Isaiah 56:1–2 (NIVUK)

2.2 Macros for typesetting scripture quotations

2.2.1 Functions

```
\ch  \ch{<chapter number>}
\ch* \ch*{<chapter number>}
```

Format a chapter number. By default these are formatted using drop text taking up two lines and the text is separated from the chapter number by a horizontal space of 0.5 em.

If the `dropchap` option is `true` (default), then this function attempts to add sufficient space for the dropped chapter when its paragraph contains only one line. The starred version suppresses this behaviour.

\ch example

```
\begin{scripture}[Exodus 20:1--2]
\ch[20]And God spoke all these words:
\begin{hanging}
\noindent\vs{2}'I am the \name{Lord} your God, who brought you out of Egypt, out of the land of slavery.
\end{hanging}
\end{scripture}
```

\ch* example

```
\begin{scripture}[Exodus 20:1--2]
\ch*[20]And God spoke all these words:
\begin{hanging}
\nohang\vs{2}'I am the \name{Lord} your God, who brought you out of Egypt, out of the land of slavery.
\end{hanging}
\end{scripture}
```

\ch example

20 And God spoke all these words:

²I am the LORD your God, who brought you out of Egypt, out of the land of slavery.

Exodus 20:1–2

\ch* example

20 And God spoke all these words:

²I am the LORD your God, who brought you out of Egypt, out of the land of slavery.

Exodus 20:1–2

\extraskip \extraskip

Add a small vertical space of `extraskip` between a paragraph. This function attempts to add additional space to avoid a clash with a drop chapter if required.

```
\begin{scripture}[Colossians 1:2]
\vs{2}To God's holy people in Colossae, the faithful brothers and sisters in Christ:
\extraskip
Grace and peace to you from God our Father.
\end{scripture}
```

²To God's holy people in Colossae, the faithful brothers and sisters in Christ:

Grace and peace to you from God our Father. **Colossians 1:2**

\added \added{<words>}

New: 2022-11-15

Some Bible translations mark out words added for clarity not found in the original language (e.g., in italics). This can be done using the `\added` function. The font and format can be set using the `added/font` and `added/format` options.

```
\begin{scripture}[John 1:18] [verse/font=\bfseries, verse/format=#1, verse/sep=0.5em, version=KJV]
\vs{18}No man hath seen God at any time, the only begotten Son, which is in the bosom of the Father, he hath declared \added{him}.
\end{scripture}
```

18 No man hath seen God at any time, the only begotten Son, which is in the bosom of the Father, he hath declared *him*.

John 1:18 (KJV)

```
\name    \name{<divine name>}
\LORD   \LORD
\GOD    \GOD
```

New: 2022-09-01

Modern Bible translations frequently represent God's personal divine name using a small capitals typeface. This can be done using the `\name` function. The font and format can be set using the `name/font` and `name/format` options. The `\LORD` and `\GOD` macros equivalent to `\name{Lord}` and `\name{God}` respectively.

Note: Watch out that trailing spaces are not eaten by `\LORD` and `\GOD`. Using `\name` is safer and semantically better.

```
\begin{scripture}[Genesis 15:1--2][version=ESV]
\ch{15}After these things the word of the
\name{Lord} came to Abram in a vision: “Fear
not, Abram, I am your shield; your reward shall
be very great.” \vs{2}But Abram said, “O Lord
\name{God}, what will you give me, for I
continue childless, and the heir of my house is
Eliezer of Damascus?”
\end{scripture}
```

15 After these things the word of the LORD came to Abram in a vision: “Fear not, Abram, I am your shield; your reward shall be very great.” ²But Abram said, “O Lord GOD, what will you give me, for I continue childless, and the heir of my house is Eliezer of Damascus?”

Genesis 15:1–2 (ESV)

```
\nofirstverse \nofirstverse
```

New: 2022-11-13

When `verse/first` is true, this causes the next `\vs` to print normally, rather than using the format specified by `verse/firstformat`. You might do this if your quote begins half way through a paragraph and the first verse should be printed normally.

```
\nohang \nohang
```

In a `hanging` environment, this function indents the first line of the paragraph a length of `hanging/hang + parindent`. Remaining lines continue to be indented by a length of `hanging/hang`.

```
\begin{scripture}[Genesis 1:10--11]
\begin{hanging}
\noindent\vs{10}God called the dry ground
‘land’, and the gathered waters he called
‘seas’. And God saw that it was good.

\nohang\vs{11}Then God said, ‘Let the land
produce vegetation: seed-bearing plants and
trees on the land that bear fruit with seed
in it, according to their various kinds.’
And it was so.
\end{hanging}
\end{scripture}
```

¹⁰God called the dry ground ‘land’, and the gathered waters he called ‘seas’. And God saw that it was good.

¹¹Then God said, ‘Let the land produce vegetation: seed-bearing plants and trees on the land that bear fruit with seed in it, according to their various kinds.’ And it was so.

Genesis 1:10–11

```
\redlettereron \redlettereron  
\redletteroff \redletteroff
```

New: 2022-08-31

Use `\redlettereron` and `\redletteroff` to mark the beginning and end of sections of text that should be attributed to Jesus speaking. Some attempt is made to ensure that the correct colour continues after an inner environment if `\redlettereron` or `\redletteroff` occurs inside the inner environment. If you experience problems with unexpected colour, try to ensure that matching `\redlettereron` and `\redletteroff` marks occur at the same group level. The colour of the text can be set using the `redletter/colour` option. These commands only have an effect when the `redletter` option is true.

```
\begin{scripture}[Matthew 21:16--17][redletter]  
  \vs{16}`Do you hear what these children are saying?  
    they asked him.  
  
  \redlettereron `Yes,' \redletteroff replied Jesus,  
  \redlettereron `have you  
  never read,  
  \begin{poetry}  
    `thinspace ``From the lips of children and infants  
      you, Lord, have called forth your praise''?  
  \end{poetry}\redletteroff  
  
  \vs{17}And he left them and went out of the city to  
    Bethany, where he spent the night.  
\end{scripture}
```

16`Do you hear what these children are saying?' they asked him.

'Yes,' replied Jesus, 'have you never read,

'From the lips of children and infants you, Lord, have called forth your praise'?

17 And he left them and went out of the city to Bethany, where he spent the night.

Matthew 21:16–17

```
\scripturesetup \scripturesetup{<options>}
```

Set default format for quotations. See section 2.4 for supported formatting `<options>`.

```
\scripturecurrentchapter \scripturecurrentchapter  
\scripturecurrentverse \scripturecurrentverse
```

New: 2022-08-07

`\scripturecurrentchapter` and `\scripturecurrentverse` globally hold the most recent values parsed to `\ch` and `\vs`. They can be initialised with `\renewcommand*` if required and could be used in hooks, for example.

```
\selah \selah
```

New: 2022-07-29

In a `poetry` environment, this function inserts *Selah* at the end of the current line or the end of the following line if there is insufficient room. See options `selah/font`, `selah/format`, `selah/sep` and `selah/text` for options controlling the output.

```
\begin{scripture}[Psalm 3:2][version=NIV84]  
  \begin{poetry}  
    \vs{2}Many are saying of me,  
      ``God will not deliver him.'' \selah  
  \end{poetry}  
\end{scripture}
```

²Many are saying of me,
 "God will not deliver him."
 Selah
 Psalm 3:2 (NIV84)

```
\scripturesetup \scripturesetup{<options>}
```

Set default format for quotations. See section 2.4 for supported formatting `<options>`.

```
\textright \textright{<text>}
```

New: 2022-08-30

This function inserts `<text>` at the end of the current line or the end of the following line if there is insufficient room. The `textright/sep` option controls the minimum allowed space before the `<text>` to be right aligned.

```
\begin{scripture}[Jeremiah 2:29]
\begin{poetry}
\vs{5}‘Why do you bring charges against me?
You have all rebelled against me,’
\textright{declares the \name{Lord}.}
\end{poetry}
\end{scripture}
```

⁵‘Why do you bring charges against
me?
You have all rebelled against
me,’
declares the LORD.
Jeremiah 2:29

```
\textscripture \textscripture[<reference>][<options>]{<quotation>}
```

New: 2023-01-07

`\textscripture` sets an inline scripture quotation. The quotation is surrounded by the values of `inline/begin` and `inline/end` which default to ‘‘\’, and \,,’’, respectively. This function also changes the defaults of some options as follows:

- `compact` is set
- `reference/align` is set to `inline`
- `reference/sep` is set to `0.5em`
- `reference/format` is set to `(#1)`
- `version/format` is set to `#1`

This function is equivalent to using the `scripture` environment with the `inline` option.

Warning: `\par` is redefined to `\relax` inside the `\textscripture` function. If you have anything other than expected macros and environments inside your `\textscripture` function TeX will likely get stuck in an infinite loop.

A famous verse in the Bible is:
`\textscripture[John 3:16][verse/hide]{\vs{16}For
God so loved the world that he gave his one and
only Son, that whoever believes in him shall not
perish but have eternal life.}.`

A famous verse in the Bible is: “For God so loved the world that he gave his one and only Son, that whoever believes in him shall not perish but have eternal life.” (**John 3:16**).

```
\vs \vs{<verse number>}
```

Format a verse number. By default these are formatted using a superscript.

2.2.2 Environments

All scripture quotations must be set within a `scripture` environment. The rest of the environments documented below are only defined with the `scripture` environment. In most cases there is a default small `<aboveskip>` and `<belowskip>` inserted above and

below these internal environments, but these are ignored if the environment is at the start or end of a `scripture` environment.

```
center \begin{center}[\langle options\rangle]
          <centred text>
        \end{center}
```

Environment for typesetting centred sections of scripture quotations.

See section 2.4.1 for supported formatting `\langle options\rangle`.

```
\begin{scripture}[Daniel 5:25]
  \vss{25}{This is the inscription that was
  written:
  \begin{center}
    \textsc{mene, mene, tekel, parsin}
  \end{center}}
\end{scripture}
```

²⁵‘This is the inscription that was
written:

MENE, MENE, TEKEL, PARSIN
Daniel 5:25

```
flushright \begin{flushright}[\langle options\rangle]
            <right aligned text>
          \end{flushright}
```

Environment for typesetting right aligned sections of scripture quotations.

See section 2.4.2 for supported formatting `\langle options\rangle`.

```
\begin{scripture}[Isaiah 40:5]
  \begin{poetry}[belowskip = 0pt]
    \vss{5}{And the glory of the \name{Lord}\ldots
    and all people will see it together.
  \end{poetry}

  \begin{flushright}[aboveskip = 0pt]
    For the mouth of the \name{Lord} \\
    has spoken.'
  \end{flushright}
\end{scripture}
```

⁵ And the glory of the LORD...
and all people will see it
together.
For the mouth of the LORD
has spoken.’
Isaiah 40:5

```
hanging \begin{hanging}[\langle options\rangle]
           <hanging text>
         \end{hanging}
```

Environment for typesetting hanging sections of scripture quotations.

See section 2.4.3 for supported formatting `\langle options\rangle`.

```
\begin{scripture}[Genesis 1:3--5]
\begin{hanging}
\vs{3}And God said, ‘Let there be light,’ and
there was light. \vs{4}God saw that the light
was good, and he separated the light from the
darkness. \vs{5}God called the light ‘day’,
and the darkness he called ‘night’. And there
was evening, and there was morn\-ing---the
first day.
\end{hanging}
\end{scripture}
```

³And God said, ‘Let there be light,’ and there was light. ⁴God saw that the light was good, and he separated the light from the darkness. ⁵God called the light ‘day’, and the darkness he called ‘night’. And there was evening, and there was morning—the first day.

Genesis 1:3–5

```
midparachap \begin{midparachap}[<options>]
  <text containing a chapter break>
\end{midparachap}
```

Environment for typesetting paragraph with a chapter break within it.

See section 2.4.4 for supported formatting *<options>*.

```
\begin{scripture}[1 Corinthians 10:31--11:1]
\begin{midparachap}
\vs{31}So whether you eat or drink or
whatever you do, do it all for the glory of
God. \vs{32}Do not cause anyone to stumble,
whether Jews, Greeks or the church of
God---\vs{33}even as I try to please everyone
in every way. For I am not seeking my own
good but the good of many, so that they may
be saved. \ch{11}Follow my example, as I
follow the example of Christ.
\end{midparachap}
\end{scripture}
```

³¹So whether you eat or drink or whatever you do, do it all for the glory of God. ³²Do not cause anyone to stumble, whether Jews, Greeks or the church of God---³³even as I try to please everyone in every way. For I am not seeking my own good but the good of many, so that they may be **11** saved. ¹Follow my example, as I follow the example of Christ.

1 Corinthians 10:31–11:1

```
narrow \begin{narrow}[<options>]
  <quotation>
\end{narrow}
```

Environment for typesetting narrow sections of scripture quotations.

See section 2.4.5 for supported formatting *<options>*.

```
\begin{scripture}[2 Kings 18:18--19]
\vs{18}They called for the king; and Eliakim
son of Hilkiah the palace administrator, Shebna
the secretary, and Joah son of Asaph the
recorder went out to them.

\vs{19}The field commander said to them, ‘Tell
Hezekiah:
\begin{narrow}
‘thinspace‘‘This is what the great king, the
king of Assyria, says: on what are you basing
this confidence of yours?
\end{narrow}
\end{scripture}
```

¹⁸They called for the king; and Eliakim son of Hilkiah the palace administrator, Shebna the secretary, and Joah son of Asaph the recorder went out to them.

¹⁹The field commander said to them, ‘Tell Hezekiah:

‘“This is what the great king,
the king of Assyria, says: on
what are you basing this confi-
dence of yours?

2 Kings 18:18–19

```
poetry \begin{poetry}[<options>]
  <first half of verse>
  <second half of verse>

  <first half of verse>
  <second half of verse>
\end{poetry}
```

Environment for typesetting poetry sections of scripture quotations.

Poetry sections of the Bible often have a first half and a parallel second half which is indented a little. These should be set on separate consecutive lines. Leaving a blank line indicates that the next line should return to the first half indent.

See section [2.4.6](#) for supported formatting *<options>*.

```
\begin{scripture}[Isaiah 1:2]
\begin{poetry}
\vs{2}Hear me, you heavens! Listen,
earth!
For the \name{Lord} has spoken:

‘I reared children and brought them up,
but they have rebelled against me.
\end{poetry}
\end{scripture}
```

²Hear me, you heavens! Listen,
earth!
For the LORD has spoken:
'I reared children and brought
them up,
but they have rebelled against
me. **Isaiah 1:2**

```
scripture \begin{scripture}[<reference>][<options>]
  <quotation>
\end{scripture}
```

Main environment for typesetting scripture quotations.

The optional *<reference>* is printed at the end of the quotation. See section [2.4](#) for supported formatting *<options>*.

```
\begin{scripture}[John 3:16][version=NIV]
\vs{16}For God so loved the world that he gave
his one and only Son, that whoever believes in
him shall not perish but have eternal life.
\end{scripture}
```

¹⁶For God so loved the world that he gave his one and only Son, that whoever believes in him shall not perish but have eternal life.

John 3:16 (NIV)

2.3 Provided hooks

-
- scripture/chap/before** The following public hooks are available:
- scripture/chap/after**
- scripture/verse/before** **scripture/chap/before** This hook is executed immediately before the `chap/font` is set
- scripture/verse/after** for the chapter.
-
- New: 2022-08-07
- scripture/chap/after** This hook is executed immediately after the `chap/sep` space is inserted.
- scripture/verse/before** This hook is executed immediately before the `verse/font` is set for the verse.
- scripture/chap/after** This hook is executed immediately after the `verse/sep` space is inserted.

The following example illustrates how these hooks could be used to place the first and last verse on the page into the header.

```

\documentclass{article}
\usepackage{scripture}
\AddToHook{scripture/chap/after}{%
    \markboth
        {Mark \scripturecurrentchapter
         :\scripturecurrentverse}
        {Mark \scripturecurrentchapter
         :\scripturecurrentverse}}
\AddToHook{scripture/verse/after}{%
    \markboth
        {Mark \scripturecurrentchapter
         :\scripturecurrentverse}
        {Mark \scripturecurrentchapter
         :\scripturecurrentverse}}
\renewcommand*\scripturecurrentchapter{\scripturecurrentchapter}
\usepackage{fancyhdr}
\pagestyle{fancy}
\fancyhf{}
\lhead{\textbf{\rightmark}}
\rhead{\textbf{\leftmark} \textbar \thepage}
\begin{document}
\noindent
\begin{scripture}
\vs{45}Instead he went out and began to talk freely, spreading the news. As a result, Jesus could no longer enter a town openly but stayed outside in lonely places. Yet the people still came to him from everywhere.

\extraskip

\ch{2}A few days later, when Jesus again entered Capernaum, the people heard that he had come home.
\end{scripture}
\end{document}

```

Mark 1:45

Mark 2:1 | 1

⁴⁵Instead he went out and began to talk freely, spreading the news. As a result, Jesus could no longer enter a town openly but stayed outside in lonely places. Yet the people still came to him from everywhere.

2 A few days later, when Jesus again entered Capernaum, the people heard that he had come home.

2.4 Options

Default formatting *<options>* can be set using `\usepackage[<options>]{scripture}` or `\scripturesetup{<options>}`. Local formatting *<options>* can be set by passing them to the various environments described above.

Note: It's not possible to pass non-expandable macros as key-value options to the optional argument of `\usepackage`. So if you want to set `font=\bfseries` as the default, you must use `\scripturesetup{font=\bfseries}`. It is not possible to use `\usepackage[font=\bfseries]{scripture}` (you will get a compile error).

<code>aboveskip</code>	<code>aboveskip = <skip></code>	<code>Default: Opt</code>
------------------------	---------------------------------------	---------------------------

(skip) inserted above the `scripture` environment.

<code>added/font</code>	<code>added/font = </code>	<code>Default: Empty</code>
-------------------------	--	-----------------------------

New: 2022-11-15 (font) used for the `\added` function.

added/format `added/format = <macro>` Default: `\emph{#1}`

New: 2022-11-15 `<macro>` used to format the words that should be highlighted as added by the translators using the `\added` function. #1 contains the text of the argument to `\added`.

belowskip `beforeskip = <skip>` Default: `0pt`

`<skip>` inserted below the `scripture` environment.

chapter/colour `chapter/colour = <colour expression>` Default: `.`

chapter/color The `\color{<colour expression>}` to be used for chapter numbers. By default the current colour is inherited. `chapter/color` is an alias for `chapter/colour`.

New: 2022-09-07 chapter/drop `chapter/drop = <boolean>` Default: `true`

Whether the chapter should be set as a drop letter taking up two lines or as a normal letter taking up one line. The value of `<boolean>` is optional and assumed to be `true` if not present. This option is the opposite of `chapter/nodrop`.

chapter/font `chapter/font = ` Default: `\bfseries`

`` used for the `\ch` function.

chapter/format `chapter/format = <macro>` Default: `#1`

New: 2022-07-28 `<macro>` used to format the `chapter` for a `scripture` quotation. #1 contains the text of the chapter.

chapter/hide `chapter/hide = <boolean>` Default: `false`

New: 2022-08-15 Whether chapters should be shown or hidden. The value of `<boolean>` is optional and assumed to be `true` if not present. This option is the opposite of `chapter/show`. Note that the `scripture/chap/before` and `scripture/chap/after` hooks are still executed when chapters are hidden.

```
\begin{scripture}[Romans 5:1--2][chapter/hide]
\ch{5}Therefore, since we have been justified
through faith, we have peace with God through
our Lord Jesus Christ, \vs{2}through whom we
have gained access by faith into this grace in
which we now stand. And we boast in the hope of
the glory of God.
\end{scripture}
```

¹Therefore, since we have been justified through faith, we have peace with God through our Lord Jesus Christ, ²through whom we have gained access by faith into this grace in which we now stand. And we boast in the hope of the glory of God.

Romans 5:1–2

chapter/nodrop `chapter/nodrop = <boolean>` Default: `false`

Whether the chapter should be set as a drop letter taking up two lines or as a normal letter taking up one line. The value of `<boolean>` is optional and assumed to be `true` if not present. This option is the opposite of `chapter/drop`.

```
\begin{scripture}[John 1:1--3][chapter/nodrop]
\ch{1}In the beginning was the Word, and the
Word was with God, and the Word was God.
\vs{2}He was with God in the beginning.
\vs{3}Through him all things were made; without
him nothing was made that has been made.
\end{scripture}
```

1 In the beginning was the Word,
and the Word was with God, and the
Word was God. ²He was with God
in the beginning. ³Through him all
things were made; without him nothing
was made that has been made.

John 1:1–3

chapter/sep `chapter/sep = <dimen>`

Default: 0.5em

`<dimen>` used to separate a `\ch` from the following text.

chapter/show `chapter/show = <boolean>`

Default: true

New: 2022-08-15 Whether chapters should be shown or hidden. The value of `<boolean>` is optional and assumed to be `true` if not present. This option is the opposite of `chapter/hide`.

chapter/showverse `chapter/showverse = <boolean>`

Default: false

New: 2022-11-14 Whether `\vs\{1\}` should be automatically inserted after `\ch`. The value of `<boolean>` is optional and assumed to be `true` if not present. See also `midparachap/showverse` and `midparachap/hideverse`. Note that `chapter/showverse` take precedence over `midparachap/hideverse`.

```
\begin{scripture}[John 1:1][chapter/showverse]
\ch{1}In the beginning was the Word, and the
Word was with God, and the Word was God.
\end{scripture}
```

1 ¹In the beginning was the Word,
and the Word was with God, and the
Word was God. **John 1:1**

colour `colour = <colour expression>`

Default: .

color `color = <colour expression>` The `\color` `<colour expression>` to be used for the `scripture` environment. By default the current colour is inherited. `color` is an alias for `colour`.

compact `compact = <boolean>`

Default: false

New: 2022-08-15 This option removes all paragraph breaks along with any `\extraskip` in the quotation so the whole quotation is a single paragraph of running prose. This option implies `chapter/nodrop` and all options relating to inner environments are ignored.

The value of `<boolean>` is optional and assumed to be `true` if not present.

Warning: This option redefines `\par` to `\relax` inside the `scripture` environment. If you have anything other than expected macros and environments inside your `scripture` environment TeX will likely get stuck in an infinite loop.

```
\begin{scripture}[Jonah 1:17--2:2a][compact]
\begin{midparachap}
\vs{17}Now the \name{Lord} provided a huge
fish to swallow Jonah, and Jonah was in the
belly of the fish three days and three
nights. \ch{2}From inside the fish Jonah
prayed to the \name{Lord} his God. \vs{2}He
said:
\end{midparachap}
\begin{poetry}
‘In my distress I called to the Lord,
and he answered me.
\end{poetry}
\end{scripture}
```

¹⁷Now the LORD provided a huge fish to swallow Jonah, and Jonah was in the belly of the fish three days and three nights. **2** From inside the fish Jonah prayed to the LORD his God. ²He said: ‘In my distress I called to the Lord, and he answered me.

Jonah 1:17–2:2a

extraskip `extraskip = <skip>` Default: `\medskipamount`
`<skip>` used for the `\extraskip` function.

font `font = ` Default: `Empty`
`` used for the `scripture` environment.

inline `inline`
New: 2023-01-07 Set the scripture quotation inline. The quotation is surrounded by the values of `inline/begin` and `inline/end` which default to ‘‘\’, and \,,’’, respectively. This option also changes the defaults of some other options as follows:

- `compact` is set
- `reference/align` is set to `inline`
- `reference/sep` is set to `0.5em`
- `reference/format` is set to `(#1)`
- `version/format` is set to `#1`

Warning: `\par` is redefined to `\relax` when the `inline` option is set. If you have anything other than expected macros and environments inside your quotation `TEX` will likely get stuck in an infinite loop.

inline/begin `inline/begin = <text>` Default: ‘‘\,
New: 2023-01-07 Text inserted at the beginning of `\textscripture` or a `scripture` environment with the `inline` option set.

inline/end `inline/end = <text>` Default: \,’’
New: 2023-01-07 Text inserted between the end of `\textscripture` or a `scripture` environment with the `inline` option set and the `<reference>` (if specified).

indent `indent = <boolean>` Default: true

Whether to indent the first line of a `scripture` environment or not by `parindent`. The value of `<boolean>` is optional and assumed to be `true` if not present. This option is the opposite of `noindent`.

language `language = <language name>` Default: Empty

New: 2022-11-02 `babel` or `polyglossia` `<language name>` to be used for the `scripture` environment. This calls `\selectlanguage{<language name>}` at the start of the environment. Make sure you have `babel` or `polyglossia` loaded and correctly set up for your specified language. If unset the current active language is used.

language/variant `language/variant = <language variant name>` Default: Empty

New: 2022-11-02 `polyglossia` `<language variant name>` to be used along with the specified `language` for the `scripture` environment. This inserts `\selectlanguage[<language variant name>]{<language name>}` at the start of the environment. Make sure you have `polyglossia` loaded and correctly set up for your specified language.

leftmargin `leftmargin = <dimen>` Default: Opt

`<dimen>` used for the left margin of the `scripture` environment.

name/font `name/font = ` Default: \scshape

New: 2022-09-01 `` used for the `\name` function.

name/format `name/format = <macro>` Default: #1

New: 2022-09-01 `<macro>` used to format the divine `name` using the `\name` function. `#1` contains the text of the argument to `\name`.

noindent `noindent = <boolean>` Default: false

Whether to indent the first line of a `scripture` environment or not by `parindent`. The value of `<boolean>` is optional and assumed to be `true` if not present. This option is the opposite of `indent`.

```
\begin{scripture}[1 Peter 3:18][noindent]
  \vs{18}For Christ also suffered once for sins,
  the righteous for the unrighteous, to bring you
  to God. He was put to death in the body but
  made alive in the Spirit.
\end{scripture}
```

¹⁸For Christ also suffered once for sins, the righteous for the unrighteous, to bring you to God. He was put to death in the body but made alive in the Spirit. **1 Peter 3:18**

parindent `parindent = <dimen>` Default: \parindent

`<dimen>` to use when indenting the first line of a paragraph in the `scripture` environment.

parskip `parskip = <skip>` Default: \parskip

`<skip>` to use between paragraphs in the `scripture` environment.

<u>redletter</u>	<code>redletter = <boolean></code>	Default: false
New: 2022-08-31	Whether to enable highlighting of Jesus' words in red. The value of <code><boolean></code> is optional and assumed to be <code>true</code> if not present. The text needs to be marked up with <code>\redletteron</code> and <code>\redletteroff</code> for this option to have any effect.	
<u>redletter/colour</u>	<code>redletter/colour = <colour expression></code>	Default: red!80!black
<u>redletter/color</u>	The l3color <code><colour expression></code> to be used for the words of Jesus when the <code>redletter</code> option is <code>true</code> . <code>\redletteron</code> and <code>\redletteroff</code> must be used to mark up the text. <code>redletter/color</code> is an alias for <code>redletter/colour</code> .	
New: 2022-08-31		
<u>reference/align</u>	<code>reference/align = inline left right</code>	Default: right
New: 2023-01-08	Set the alignment of the reference. For <code>left</code> and <code>right</code> the reference will not break across lines, but a line break is permitted for <code>inline</code> .	
<u>reference/colour</u>	<code>reference/colour = <colour expression></code>	Default: .
<u>reference/color</u>	The l3color <code><colour expression></code> to be used for the reference and version. By default the current colour is inherited. <code>reference/color</code> is an alias for <code>reference/colour</code> .	
New: 2022-09-07		
<u>reference/font</u>	<code>reference/font = </code>	Default: \bfseries
	<code></code> used when printing the <code>reference</code> for a <code>scripture</code> quotation.	
<u>reference/format</u>	<code>reference/format = <macro></code>	Default: #1
	<code><macro></code> used to format the <code>reference</code> for a <code>scripture</code> quotation. #1 contains the text of the <code>reference</code> and <code>version</code> (if specified).	
<u>reference/newline</u>	<code>reference/newline</code>	
New: 2023-01-08	Always push the <code>reference</code> to a newline even if there is space for it to fit on the last line of the quotation. The option sets <code>reference/sep</code> to <code>\ linewidth</code> so there is never room for the reference on the final line of the quotation.	
<u>reference/sep</u>	<code>reference/sep = <dimen></code>	Default: 2em
	The minimum <code><dimen></code> allowed between the end of a <code>scripture</code> quotation and its <code>reference</code> before the <code>reference</code> is pushed to the following line.	
<u>rightmargin</u>	<code>rightmargin = <dimen></code>	Default: Opt
	<code><dimen></code> used for the right margin of the <code>scripture</code> environment.	
<u>selah/font</u>	<code>selah/font = </code>	Default: \itshape
	<code></code> used when printing <code>\selah</code> in a <code>poetry</code> environment.	
<u>selah/format</u>	<code>selah/format = <macro></code>	Default: #1
	<code><macro></code> used to format the <code>\selah</code> in a <code>poetry</code> environment. #1 contains the value of <code>selah/text</code> .	

selah/sep `selah/sep = <dimen>` Default: 1em

The minimum `<dimen>` allowed between the end of a poetry line and *Selah* before the *Selah* is pushed to the following line.

selah/text `selah/text = <text>` Default: Selah

`<text>` used to for \selah in a poetry environment.

textright/sep `textright/sep = <dimen>` Default: 1em

New: 2022-08-30 The minimum `<dimen>` allowed between the end of a line and text aligned to the right with \textright before the right aligned text is pushed to the following line.

verse/colour `verse/colour = <colour expression>` Default: .

verse/color `verse/color = <colour expression>` The \color{<colour expression>} to be used for verse numbers. By default the current colour is inherited. `verse/color` is an alias for `verse/colour`.

verse/first `verse/first = <boolean>` Default: false

New: 2022-11-13 In prose sections, print the verse number in a different format if it is at the start of the paragraph. The format and separation between verse and text are controlled with the `verse/firstformat` and `verse/firstsep` options. Use \noversefirst to suppress this at the next verse (e.g., if your quote starts mid-way though a paragraph and a normal verse should be printed). The value of `<boolean>` is optional and assumed to be true if not present.

```
\begin{scripture}[Luke 18:25--28][noindent,
  verse/first, version=NRSV]
\nofirstverse\vs{25}Indeed, it is easier for a
camel to go through the eye of a needle than for
someone who is rich to enter the kingdom of
God.''
\vs{26}Those who heard it said, ``Then who can
be saved?'' \vs{27}He replied, ``What is
impossible for mortals is possible for God.''
\vs{28}Then Peter said, ``Look, we have left our
homes and followed you.''
\end{scripture}
```

²⁵Indeed, it is easier for a camel to go through the eye of a needle than for someone who is rich to enter the kingdom of God.”

26 Those who heard it said, “Then who can be saved?” ²⁷He replied, “What is impossible for mortals is possible for God.”

28 Then Peter said, “Look, we have left our homes and followed you.”

Luke 18:25–28 (NRSV)

verse/firstformat `verse/firstformat = <macro>` Default: #1

New: 2022-11-13 `<macro>` used to format the first \vs in a paragraph. #1 contains the argument of \vs. Only used if `verse/first` is true.

verse/firstsep `verse/firstsep = <dimen>` Default: 0.5em

New: 2022-11-13 `<dimen>` used to separate the first \vs in a paragraph from the following text. Only used if `verse/first` is true.

verse/font `verse/font = ` Default: Empty
 `` used for the `\vs` function.

verse/format `verse/format = <macro>` Default: #1
 `<macro>` used to format the `\vs` function. #1 contains the argument of `\vs`.

verse/hide `verse/hide = <boolean>` Default: false

New: 2022-08-15 Whether verses should be shown or hidden. The value of `<boolean>` is optional and assumed to be `true` if not present. This option is the opposite of `verse/show`. Note that the `scripture/verse/before` and `scripture/verse/after` hooks are still executed when verses are hidden.

```
\begin{scripture}[Colossians 1:15--16][verse/hide]
\vs{15}The Son is the image of the invisible
God, the firstborn over all creation.
\vs{16}For in him all things were created:
things in heaven and on earth, visible and
invisible, whether thrones or powers or rulers
or authorities; all things have been created
through him and for him.
\end{scripture}
```

The Son is the image of the invisible God, the firstborn over all creation. For in him all things were created: things in heaven and on earth, visible and invisible, whether thrones or powers or rulers or authorities; all things have been created through him and for him.

Colossians 1:15–16

verse/sep `verse/sep = <dimen>` Default: 0.05 em

New: 2022-07-28 `<dimen>` used to separate a `\vs` from the following text.

verse/show `verse/show = <boolean>` Default: true

New: 2022-08-15 Whether verses should be shown or hidden. The value of `<boolean>` is optional and assumed to be `true` if not present. This option is the opposite of `verse/hide`.

version `version = <version>` Default: Empty
 `<version>` added to the reference for a scripture quotation.

version/delim `version/delim = <delim>` Default: { }
 `<delim>` to use between the reference and the version of a scripture quotation.

version/format `version/format = <macro>` Default: (#1)
 `<macro>` used to format the version for a scripture quotation. #1 contains the text of the version.

2.4.1 Options for the `center` environment

If these options are passed directly to the `center` environment rather than to the package, `\scripturesetup` or the `scripture` environment, then the `center/` prefix should be dropped.

<u>center/aboveskip</u>	<code>center/aboveskip = <skip></code>	Default: \medskipamount
	<i><skip></i> inserted above the <code>center</code> environment.	
<u>center/belowskip</u>	<code>center/belowskip = <skip></code>	Default: \medskipamount
	<i><skip></i> inserted below the <code>center</code> environment.	
<u>center/leftmargin</u>	<code>center/leftmargin = <dimen></code>	Default: 0pt
	<i><dimen></i> used for the left margin of the <code>center</code> environment.	
<u>center/rightmargin</u>	<code>center/rightmargin = <dimen></code>	Default: 0pt
	<i><dimen></i> used for the right margin of the <code>center</code> environment.	

2.4.2 Options for the `flushright` environment

If these options are passed directly to the `flushright` environment rather than to the package, `\scripturesetup` or the `scripture` environment, then the `flushright/` prefix should be dropped.

<u>flushright/aboveskip</u>	<code>flushright/aboveskip = <skip></code>	Default: \medskipamount
	<i><skip></i> inserted above the <code>flushright</code> environment.	
<u>flushright/belowskip</u>	<code>flushright/belowskip = <skip></code>	Default: \medskipamount
	<i><skip></i> inserted below the <code>flushright</code> environment.	
<u>flushright/leftmargin</u>	<code>flushright/leftmargin = <dimen></code>	Default: 0pt
	<i><dimen></i> used for the left margin of the <code>flushright</code> environment.	
<u>flushright/rightmargin</u>	<code>flushright/rightmargin = <dimen></code>	Default: 0pt
	<i><dimen></i> used for the right margin of the <code>flushright</code> environment.	

2.4.3 Options for the `hanging` environment

If these options are passed directly to the `hanging` environment rather than to the package, `\scripturesetup` or the `scripture` environment, then the `hanging/` prefix should be dropped.

<u>hanging/aboveskip</u>	<code>hanging/aboveskip = <skip></code>	Default: \medskipamount
	<i><skip></i> inserted above the <code>hanging</code> environment.	
<u>hanging/belowskip</u>	<code>hanging/belowskip = <skip></code>	Default: \medskipamount
	<i><skip></i> inserted below the <code>hanging</code> environment.	
<u>hanging/hang</u>	<code>hanging/hang = <dimen></code>	Default: 2em
	<i><dimen></i> used for the indent of subsequent lines of the <code>hanging</code> environment.	

`hanging/leftmargin` `hanging/leftmargin = <dimen>` Default: 1em
 `<dimen>` used for the left margin of the `hanging` environment.

`hanging/rightmargin` `hanging/rightmargin = <dimen>` Default: 1em
 `<dimen>` used for the right margin of the `hanging` environment.

2.4.4 Options for the `midparachap` environment

If these options are passed directly to the `midparachap` environment rather than to the package, `\scripturesetup` or the `scripture` environment, then the `midparachap/` prefix should be dropped.

`midparachap/hideverse` `midparachap/hideverse = <boolean>` Default: false
Whether a `\vs{1}` should automatically be inserted after a `\ch` when the `\ch` occurs mid-paragraph. This also affects `\ch` in `poetry` environments. `\extraskip` begins a new paragraph in a `poetry` environment. The value of `<boolean>` is optional and assumed to be `true` if not present. This option is the opposite of `midparachap/showverse`. See also `chapter/showverse`.

```
\begin{scripture}[Hosea 11:12--12:1]%
  [midparachap/hideverse]
  \begin{poetry}
    \vs{12}Ephraim has surrounded me with lies,
    Israel with deceit.
    And Judah is unruly against God,
    even against the faithful Holy One.
    \ch{12}Ephraim feeds on the wind;
    he pursues the east wind all day
    and multiplies lies and violence.
    He makes a treaty with Assyria
    and sends olive oil to Egypt.
  \end{poetry}
\end{scripture}
```

¹²Ephraim has surrounded me with lies,
Israel with deceit.
And Judah is unruly against God,
even against the faithful Holy One.

12 Ephraim feeds on the wind;
he pursues the east wind all day
and multiplies lies and violence.
He makes a treaty with Assyria
and sends olive oil to Egypt.

Hosea 11:12–12:1

`midparachap/showverse` `midparachap/showverse = <boolean>` Default: true
Whether a `\vs{1}` should automatically be inserted after a `\ch` when the `\ch` occurs mid-paragraph. This also affects `\ch` in `poetry` environments. `\extraskip` begins a new paragraph in a `poetry` environment. The value of `<boolean>` is optional and assumed to be `true` if not present. This option is the opposite of `midparachap/hideverse`. See also `chapter/showverse`.

2.4.5 Options for the `narrow` environment

If these options are passed directly to the `narrow` environment rather than to the package, `\scripturesetup` or the `scripture` environment, then the `narrow/` prefix should be dropped.

<u>narrow/aboveskip</u>	narrow/aboveskip = <i><skip></i>	Default: \medskipamount
	<i><skip></i> inserted above the narrow environment.	
<u>narrow/belowskip</u>	narrow/belowskip = <i><skip></i>	Default: \medskipamount
	<i><skip></i> inserted below the narrow environment.	
<u>narrow/leftmargin</u>	narrow/leftmargin = <i><dimen></i>	Default: 1em
	<i><dimen></i> used for the left margin of the narrow environment.	
<u>narrow/rightmargin</u>	narrow/rightmargin = <i><dimen></i>	Default: 1em
	<i><dimen></i> used for the right margin of the narrow environment.	

2.4.6 Options for the **poetry** environment

If these options are passed directly to the **poetry** environment rather than to the package, **\scripturesetup** or the **scripture** environment, then the **poetry/** prefix should be dropped.

<u>poetry/aboveskip</u>	poetry/aboveskip = <i><skip></i>	Default: \medskipamount
	<i><skip></i> inserted above the poetry environment.	
<u>poetry/belowskip</u>	poetry/belowskip = <i><skip></i>	Default: \medskipamount
	<i><skip></i> inserted below the poetry environment.	
<u>poetry/bigindent</u>	poetry/bigindent = <i><dimen></i>	Default: 4em
	<i><dimen></i> used for the indent subsequent lines of a line of poetry in a poetry environment if it needs to flow on to the following line.	
<u>poetry/indent</u>	poetry/indent = <i><dimen></i>	Default: 1em
	<i><dimen></i> used for the second half of a line of poetry in a poetry environment.	
<u>poetry/leftmargin</u>	poetry/leftmargin = <i><dimen></i>	Default: 1em
	<i><dimen></i> used for the left margin of the poetry environment.	
<u>poetry/rightmargin</u>	poetry/rightmargin = <i><dimen></i>	Default: 0pt
	<i><dimen></i> used for the right margin of the poetry environment.	
<u>poetry/verse/left</u>	poetry/verse/left = <i><boolean></i>	Default: false
New: 2022-07-31	Align verse numbers in poetry environments at the left margin of the scripture environment. This option is the opposite of poetry/verse/right .	

```

\begin{scripture}[Atcs 15:15--18]%
  [poetry/leftmargin=2em, poetry/verse/left]
  \vs{15}The words of the prophets are in
  agreement with this, as it is written:
  \begin{poetry}
    \vs{16}`\thinspaceAfter this I will return
    and rebuild David's fallen tent.

    Its ruins I will rebuild,
    and I will restore it,

    \vs{17}that the rest of mankind may seek the Lord,
    even all the Gentiles who bear my name,
    says the Lord, who does these things'---%
    \vs{18}things known from long ago.
  \end{poetry}
\end{scripture}

```

¹⁵The words of the prophets are in agreement with this, as it is written:

¹⁶ “After this I will return and rebuild David's fallen tent.
Its ruins I will rebuild, and I will restore it,
¹⁷ that the rest of mankind may seek the Lord, even all the Gentiles who bear my name, says the Lord, who does these things”—
¹⁸ things known from long ago.

Atcs 15:15–18

poetry/verse/right `poetry/verse/right = <boolean>`

Default: true

New: 2022-07-31 Align verse numbers in `poetry` environments at the left margin of the `poetry` environment. The verse numbers overlap to the left. This option is the opposite of `poetry/verse/left`.

poetry/verse/sep `poetry/verse/sep = <dimen>`

Default: 0.05 em

New: 2022-07-31 `<dimen>` used to separate a `\vs` from the following text in a `poetry` environment. This is only used for verses at the start of a line.

3 Implementation

```

1  <*package>
2  <@@=scripture>
3  \NeedsTeXFormat{LaTeX2e}[2022-06-01]
4  \ProvidesExplPackage{scripture}{2023/01/08}{1.3}
5  {Format Scripture Quotations (DCP)}

```

3.1 Messages

`scripture` environments along with all internal environments can not be nested.

```

6  \msg_new:nnnn { scripture } { nested-environment }
7  { Nesting~of~scripture~environments~not~supported. }
8  { You~have~tried~to~nest~a~scripture~environment~or~\\
9   one~of~its~internal~environments,~which~is~not~supported. }

```

Make sure polyglossia languages and variants are set up.

```

10 \msg_new:nnnn { scripture } { language-error }
11  { Language~`#1`~not~set~up. }
12  { Language~`#1`~has~not~been~set~up.~Make~sure~you~set~up~languages~
13   before~using~the~language~option~of~the~scripture~environment. }

```

Warn if a language is requested and neither babel nor polyglossia is loaded.

```
14 \msg_new:nnnn { scripture } { language-warning }
15   { Language-requested-without-support. }
16   { You-have-requested-language=#1,~but~neither-babel-nor-polyglossia-
17     have~been~loaded~and~set~up.~Ignoring~option~language=#1. }
```

3.2 Options

Key-value settings for the `scripture` environment and its inner environments.

```
18 \keys_define:nn { scripture }
19   {
20     , aboveskip           .tl_set:N      = \l__scripture_aboveskip_tl
21     , aboveskip           .value_required:n = true
22     , aboveskip           .initial:n    = \c_zero_skip
23     , added / font        .tl_set:N      = \l__scripture_added_font_tl
24     , added / font        .value_required:n = true
25     , added / font        .initial:n    =
26     , added / format      .cs_set:Np    = \__scripture_added_format:n #1
27     , added / format      .value_required:n = true
28     , added / format      .initial:n    = \emph { #1 }
29     , belowskip            .tl_set:N      = \l__scripture_bellowskip_tl
30     , belowskip            .value_required:n = true
31     , belowskip            .initial:n    = \c_zero_skip
32     , colour               .tl_set:N      = \l__scripture_colour_tl
33     , colour               .value_required:n = true
34     , colour               .initial:n    =
35     , color                .meta:n       = { colour = { #1 } }
36     , compact              .bool_set:N  = \l__scripture_compact_bool
37     , compact              .default:n   = true
38     , compact              .initial:n   = false
39     , chapter / font       .tl_set:N      = \l__scripture_chap_font_tl
40     , chapter / font       .value_required:n = true
41     , chapter / font       .initial:n   = \bfseries
42     , chapter / colour     .tl_set:N      = \l__scripture_chapter_colour_tl
43     , chapter / colour     .value_required:n = true
44     , chapter / colour     .initial:n   =
45     , chapter / color      .meta:n       = { chapter / colour = { #1 } }
46     , chapter / drop       .bool_set:N  = \l__scripture_chap_drop_bool
47     , chapter / drop       .default:n   = true
48     , chapter / drop       .initial:n   = true
49     , chapter / format     .cs_set:Np    = \__scripture_chap_format:n #1
50     , chapter / format     .value_required:n = true
51     , chapter / format     .initial:n   = #1
52     , chapter / hide       .bool_set_inverse:N = \l__scripture_chap_show_bool
53     , chapter / hide       .default:n   = true
54     , chapter / nodrop     .bool_set_inverse:N = \l__scripture_chap_drop_bool
55     , chapter / nodrop     .default:n   = true
56     , chapter / sep        .tl_set:N      = \l__scripture_chap_sep_tl
57     , chapter / sep        .value_required:n = true
58     , chapter / sep        .initial:n   = 0.5 em
59     , chapter / show       .bool_set:N  = \l__scripture_chap_show_bool
60     , chapter / show       .default:n   = true
61     , chapter / show       .initial:n   = true
```

```

62 , chapter / showverse .bool_set:N = \l__scripture_chap_show_verse_bool
63 , chapter / showverse .default:n = true
64 , chapter / showverse .initial:n = false
65 , extraskip .tl_set:N = \l__scripture_extraskip_tl
66 , extraskip .value_required:n = true
67 , extraskip .initial:n = \medskipamount
68 , font .tl_set:N = \l__scripture_font_tl
69 , font .value_required:n = true
70 , font .initial:n =
71 , indent .bool_set:N = \l__scripture_indent_bool
72 , indent .default:n = true
73 , indent .initial:n = true
74 , _inline .bool_set:N = \l__scripture_inline_bool
75 , _inline .initial:n = false
76 , inline .meta:n = {
77 , inline _inline = true ,
78 , inline compact ,
79 , inline reference / format = (##1) ,
80 , inline reference / align = inline ,
81 , inline reference / sep = 0.5 em,
82 , inline version / format = ##1
83 }
84 , inline .value_forbidden:n = true
85 , inline / begin .tl_set:N = \l__scripture_inline_begin_tl
86 , inline / begin .value_required:n = true
87 , inline / begin .initial:n = ‘\,
88 , inline / end .tl_set:N = \l__scripture_inline_end_tl
89 , inline / end .value_required:n = true
90 , inline / end .initial:n = \,’
91 , language .tl_set:N = \l__scripture_language_tl
92 , language .value_required:n = true
93 , language .initial:n =
94 , language / variant .tl_set:N = \l__scripture_language_variant_tl
95 , language / variant .value_required:n = true
96 , language / variant .initial:n =
97 , leftmargin .tl_set:N = \l__scripture_leftmargin_tl
98 , leftmargin .value_required:n = true
99 , leftmargin .initial:n = \c_zero_dim
100 , name / font .tl_set:N = \l__scripture_name_font_tl
101 , name / font .value_required:n = true
102 , name / font .initial:n = \scshape
103 , name / format .cs_set:Np = \l__scripture_name_format:n #1
104 , name / format .value_required:n = true
105 , name / format .initial:n = #1
106 , noindent .bool_set_inverse:N = \l__scripture_indent_bool
107 , noindent .default:n = true
108 , parindent .tl_set:N = \l__scripture_parindent_tl
109 , parindent .value_required:n = true
110 , parindent .initial:n = \parindent
111 , parskip .tl_set:N = \l__scripture_parskip_tl
112 , parskip .value_required:n = true
113 , parskip .initial:n = \parskip
114 , redletter .bool_set:N = \l__scripture_red_letter_bool
115 , redletter .default:n = true

```

```

116   , redletter           .initial:n      = false
117   , redletter / colour .tl_set:N       = \l__scripture_red_letter_colour_tl
118   , redletter / colour .value_required:n = true
119   , redletter / colour .initial:n      = red!80!black
120   , redletter / color  .meta:n        = { redletter / colour = { #1 } }
121   , reference / align   .choices:nn    = { inline, left, right }
122
123
124
125
126
127   , reference / align   .value_required:n = true
128   , reference / align   .initial:n      = right
129   , reference / colour  .tl_set:N       = \l__scripture_ref_colour_tl
130   , reference / colour  .value_required:n = true
131   , reference / colour  .initial:n      =
132   , reference / color   .meta:n        = { reference / colour = { #1 } }
133   , reference / font    .tl_set:N       = \l__scripture_ref_font_tl
134   , reference / font    .value_required:n = true
135   , reference / font    .initial:n      = \bfseries
136   , reference / format  .cs_set:Np     = \__scripture_ref_format:n #1
137   , reference / format  .value_required:n = true
138   , reference / format  .initial:n      = #1
139   , reference / newline .meta:n        = { reference / sep = \linewidth }
140   , reference / newline .value_forbidden:n = true
141   , reference / sep     .tl_set:N       = \l__scripture_ref_sep_tl
142   , reference / sep     .value_required:n = true
143   , reference / sep     .initial:n      = 2 em
144   , rightmargin          .tl_set:N       = \l__scripture_rightmargin_tl
145   , rightmargin          .value_required:n = true
146   , rightmargin          .initial:n      = \c_zero_dim
147   , selah / text         .tl_set:N       = \l__scripture_selah_text_tl
148   , selah / text         .value_required:n = true
149   , selah / text         .initial:n      = Selah
150   , selah / font         .tl_set:N       = \l__scripture_selah_font_tl
151   , selah / font         .value_required:n = true
152   , selah / font         .initial:n      = \itshape
153   , selah / format        .cs_set:Np     = \__scripture_selah_format:n #1
154   , selah / format        .value_required:n = true
155   , selah / format        .initial:n      = #1
156   , selah / sep          .tl_set:N       = \l__scripture_selah_sep_tl
157   , selah / sep          .value_required:n = true
158   , selah / sep          .initial:n      = 1 em
159   , textright / sep        .tl_set:N       = \l__scripture_text_right_sep_tl
160   , textright / sep        .value_required:n = true
161   , textright / sep        .initial:n      = 1 em
162   , verse / colour         .tl_set:N       = \l__scripture_verse_colour_tl
163   , verse / colour         .value_required:n = true
164   , verse / colour         .initial:n      =
165   , verse / color          .meta:n        = { verse / colour = { #1 } }
166   , verse / first          .bool_set:N    = \l__scripture_verse_first_bool
167   , verse / first          .default:n     = true
168   , verse / first          .initial:n      = false
169   , verse / firstformat    .cs_set:Np     = \__scripture_verse_first_format:n #1

```

```

170 , verse / firstformat .value_required:n = true
171 , verse / firstformat .initial:n = #1
172 , verse / firstsep .tl_set:N = \l__scripture_verse_first_sep_tl
173 , verse / firstsep .value_required:n = true
174 , verse / firstsep .initial:n = 0.5em
175 , verse / font .tl_set:N = \l__scripture_verse_font_tl
176 , verse / font .value_required:n = true
177 , verse / font .initial:n =
178 , verse / format .cs_set:Np = \__scripture_verse_format:n #1
179 , verse / format .value_required:n = true
180 , verse / format .initial:n = \textsuperscript{#1}
181 , verse / hide .bool_set_inverse:N = \l__scripture_verse_show_bool
182 , verse / hide .default:n = true
183 , verse / sep .tl_set:N = \l__scripture_verse_sep_tl
184 , verse / sep .value_required:n = true
185 , verse / sep .initial:n = 0.05 em
186 , verse / show .bool_set:N = \l__scripture_verse_show_bool
187 , verse / show .default:n = true
188 , verse / show .initial:n = true
189 , version .tl_set:N = \l__scripture_version_tl
190 , version .value_required:n = true
191 , version .initial:n =
192 , version / delim .tl_set:N = \l__scripture_version_delim_tl
193 , version / delim .value_required:n = true
194 , version / delim .initial:n = \c_space_tl
195 , version / format .cs_set:Np = \__scripture_version_format:n #1
196 , version / format .value_required:n = true
197 , version / format .initial:n = (#1)

```

Options for the center environment.

```

198 , center / aboveskip .tl_set:N = \l__scripture_center_aboveskip_tl
199 , center / aboveskip .value_required:n = true
200 , center / aboveskip .initial:n = \medskipamount
201 , center / belowskip .tl_set:N = \l__scripture_center_beforeskip_tl
202 , center / belowskip .value_required:n = true
203 , center / belowskip .initial:n = \medskipamount
204 , center / leftmargin .tl_set:N = \l__scripture_center_leftmargin_tl
205 , center / leftmargin .value_required:n = true
206 , center / leftmargin .initial:n = \c_zero_dim
207 , center / rightmargin .tl_set:N = \l__scripture_center_rightmargin_tl
208 , center / rightmargin .value_required:n = true
209 , center / rightmargin .initial:n = \c_zero_dim

```

Options for the flushright environment.

```

210 , flushright / aboveskip .tl_set:N = \l__scripture_flushright_aboveskip_tl
211 , flushright / aboveskip .value_required:n = true
212 , flushright / aboveskip .initial:n = \medskipamount
213 , flushright / belowskip .tl_set:N = \l__scripture_flushright_beforeskip_tl
214 , flushright / belowskip .value_required:n = true
215 , flushright / belowskip .initial:n = \medskipamount
216 , flushright / leftmargin .tl_set:N = \l__scripture_flushright_leftmargin_tl
217 , flushright / leftmargin .value_required:n = true
218 , flushright / leftmargin .initial:n = \c_zero_dim
219 , flushright / rightmargin .tl_set:N = \l__scripture_flushright_rightmargin_tl
220 , flushright / rightmargin .value_required:n = true

```

```

221      , flushright / rightmargin .initial:n      = \c_zero_dim
Options for the hanging environment.
222      , hanging / aboveskip     .tl_set:N      = \l__scripture_hanging_aboveskip_tl
223      , hanging / aboveskip     .value_required:n = true
224      , hanging / aboveskip     .initial:n      = \medskipamount
225      , hanging / belowskip    .tl_set:N      = \l__scripture_hanging_beforeskip_tl
226      , hanging / belowskip    .value_required:n = true
227      , hanging / belowskip    .initial:n      = \medskipamount
228      , hanging / hang         .tl_set:N      = \l__scripture_hanging_hang_tl
229      , hanging / hang         .value_required:n = true
230      , hanging / hang         .initial:n      = 2 em
231      , hanging / leftmargin   .tl_set:N      = \l__scripture_hanging_leftmargin_tl
232      , hanging / leftmargin   .value_required:n = true
233      , hanging / leftmargin   .initial:n      = 1 em
234      , hanging / rightmargin  .tl_set:N      = \l__scripture_hanging_rightmargin_tl
235      , hanging / rightmargin  .value_required:n = true
236      , hanging / rightmargin  .initial:n      = \c_zero_dim

Options for the mid-paragraph chapters (including the midparachap environment).
237      , midparachap / hideverse .bool_set_inverse:N = \l__scripture_midparachap_show_verse_bo
238      , midparachap / hideverse .default:n      = true
239      , midparachap / showverse .bool_set:N      = \l__scripture_midparachap_show_verse_bo
240      , midparachap / showverse .default:n      = true
241      , midparachap / showverse .initial:n      = true

Options for the narrow environment.
242      , narrow / aboveskip     .tl_set:N      = \l__scripture_narrow_aboveskip_tl
243      , narrow / aboveskip     .value_required:n = true
244      , narrow / aboveskip     .initial:n      = \medskipamount
245      , narrow / belowskip    .tl_set:N      = \l__scripture_narrow_beforeskip_tl
246      , narrow / belowskip    .value_required:n = true
247      , narrow / belowskip    .initial:n      = \medskipamount
248      , narrow / leftmargin   .tl_set:N      = \l__scripture_narrow_leftmargin_tl
249      , narrow / leftmargin   .value_required:n = true
250      , narrow / leftmargin   .initial:n      = 1 em
251      , narrow / rightmargin  .tl_set:N      = \l__scripture_narrow_rightmargin_tl
252      , narrow / rightmargin  .value_required:n = true
253      , narrow / rightmargin  .initial:n      = 1 em

Options for the poetry environment.
254      , poetry / aboveskip     .tl_set:N      = \l__scripture_poetry_aboveskip_tl
255      , poetry / aboveskip     .value_required:n = true
256      , poetry / aboveskip     .initial:n      = \medskipamount
257      , poetry / belowskip    .tl_set:N      = \l__scripture_poetry_beforeskip_tl
258      , poetry / belowskip    .value_required:n = true
259      , poetry / belowskip    .initial:n      = \medskipamount
260      , poetry / bigindent    .tl_set:N      = \l__scripture_poetry_big_indent_tl
261      , poetry / bigindent    .value_required:n = true
262      , poetry / bigindent    .initial:n      = 4 em
263      , poetry / indent       .tl_set:N      = \l__scripture_poetry_indent_tl
264      , poetry / indent       .value_required:n = true
265      , poetry / indent       .initial:n      = 1 em
266      , poetry / leftmargin   .tl_set:N      = \l__scripture_poetry_leftmargin_tl
267      , poetry / leftmargin   .value_required:n = true
268      , poetry / leftmargin   .initial:n      = 1 em

```

```

269     , poetry / rightmargin      .tl_set:N      = \l__scripture_poetry_rightmargin_tl
270     , poetry / rightmargin      .value_required:n = true
271     , poetry / rightmargin      .initial:n    = \c_zero_dim
272     , poetry / verse / left    .bool_set_inverse:N = \l__scripture_poetry_verse_right_bool
273     , poetry / verse / left    .default:n    = true
274     , poetry / verse / right   .bool_set:N      = \l__scripture_poetry_verse_right_bool
275     , poetry / verse / right   .default:n    = true
276     , poetry / verse / right   .initial:n    = true
277     , poetry / verse / sep     .tl_set:N      = \l__scripture_poetry_verse_sep_tl
278     , poetry / verse / sep     .value_required:n = true
279     , poetry / verse / sep     .initial:n    = 0.05 em
280 }

```

Process package options.

```
281 \ProcessKeyOptions
```

3.3 Hooks

scripture/chap/before
scripture/chap/after
scripture/verse/before
scripture/verse/after

```

282 \hook_new_pair:nn { scripture / chap / before } { scripture / chap / after }
283 \hook_new_pair:nn { scripture / verse / before } { scripture / verse / after }

```

(End definition for *scripture/chap/before* and others. These variables are documented on page 11.)

3.4 The main scripture environment

\l__scripture_active_bool
\l__scripture_active_inner_bool

```

284 \bool_new:N \l__scripture_active_bool
285 \bool_new:N \l__scripture_active_inner_bool

```

(End definition for *\l__scripture_active_bool* and *\l__scripture_active_inner_bool*.)

\l__scripture_clubpenalty_saved_int

Holds saved club penalty so we can change and restore it around chapter breaks.

```
286 \int_new:N \l__scripture_clubpenalty_saved_int
```

(End definition for *\l__scripture_clubpenalty_saved_int*.)

_\scripture_extra_skip:

Insert a little extra vertical space between two paragraphs. This function tests if the previous paragraph is only one line in length and began with a *\ch* function. If this condition is met, more space is added if necessary to avoid the following paragraph clashing with the drop chapter.

```

287 \cs_new_protected:Nn \_\scripture_extra_skip:
288 {
289     \int_compare:nNnT
290         \g__scripture_chap_par_prevgraf_int = 1
291     {
292         \dim_compare:nNnT
293             { \parskip + \glueexpr \l__scripture_extraskip_tl } < \baselineskip
294         {
295             \addvspace { \baselineskip }
296         }
297         \int_gzero:N \g__scripture_chap_par_prevgraf_int

```

```

298      }
299      \addvspace { \l__scripture_extraskip_t1 }
300  }

```

(End definition for `_scripture_extra_skip`.)

`_scripture_text_right:nn` Align a word to the right and finish a paragraph, pushing to the next line if there is not space for the word.

```

301 \cs_new_protected:Nn \_scripture_text_right:nn
302 {
303     \bool_lazy_or:nnTF
304     { \str_if_eq_p:Vn \l__scripture_currenvir_str { flushright } }
305     { \str_if_eq_p:Vn \l__scripture_currenvir_str { center } }
306     {
307         \unskip
308         \break
309         \strut
310         \hfill
311         #2
312         \para_end:
313     }
314     {
315         {
316             \unskip
317             \hfil
318             \penalty 50
319             \skip_horizontal:n { #1 }
320             \hbox:n {}
321             \nobreak
322             \hfill
323             #2
324             \skip_zero:N \parfillskip
325             \int_zero:N \finalhyphendemerits
326             \para_end:
327         }
328     }
329 }

```

(End definition for `_scripture_text_right:nn`.)

3.4.1 Formatting and printing quotation references

`\l__scripture_ref_box` Box to hold the formatted reference.

```
330 \box_new:N \l__scripture_ref_box
```

(End definition for `\l__scripture_ref_box`.)

`_scripture_format_full_ref:n` Format a scripture quotation with its reference.

```

331 \cs_new_protected:Nn \_scripture_format_full_ref:n
332 {
333     \group_begin:
334     \l__scripture_ref_font_t1
335     \str_if_eq:VnF \l__scripture_ref_colour_t1 { . }
336     { \exp_args:NV \color_select:n \l__scripture_ref_colour_t1 }

```

```

337      \__scripture_ref_format:n
338      {
339          #1
340          \tl_if_empty:NF \l__scripture_version_tl
341          {
342              \l__scripture_version_delim_tl
343              \__scripture_version_format:n { \l__scripture_version_tl }
344          }
345      }
346      \group_end:
347  }
```

(End definition for `__scripture_format_full_ref:n`.)

`__scripture_reference:n` Output the reference for the Scripture quotation.

```

348  \cs_new_protected:Nn \__scripture_reference:n
349  {
350      \hbox_set:Nn \l__scripture_ref_box
351      {
352          \__scripture_format_full_ref:n { #1 }
353      }
354  }
```

Since the `poetry` environment uses `__scripture_obeylines`: there is always an extra `\parskip` when a `scripture` quotation ends with a `poetry` environment.

```

354      \bool_if:NT \g__scripture_poetry_end_bool
355      { \skip_vertical:n { -\parskip } }
356      \dim_compare:nNnT
357      { \box_wd:N \l__scripture_ref_box + \g__scripture_final_line_dim + \l__scripture_ref_s
358      >
359          \linewidth
360      { \skip_vertical:N \baselineskip } }
```

If a `scripture` quotation ends with an inner environment, there will be an extra space of `\baselineskip`.

```

361      \int_compare:nNnT \prevgraf = \c_zero_int
362      { \skip_vertical:n { -\baselineskip } }
363      \tl_if_eq:NnT \l__scripture_ref_align_tl { right }
364      { \hfill }
365      \tl_if_eq:NnT \l__scripture_ref_align_tl { left }
366      {
367          \mode_leave_vertical:
368          \dim_compare:nNnT
369          { \box_wd:N \l__scripture_ref_box + \g__scripture_final_line_dim + \l__scripture_r
370          <
371              \linewidth
372              { \skip_horizontal:n { \g__scripture_final_line_dim + \l__scripture_ref_sep_t
373          }
374          \box_use:N \l__scripture_ref_box
375      }
```

(End definition for `__scripture_reference:n`.)

3.4.2 Red lettering

\g_scripture_red_letter_active_bool Flag indicating if currently in a red letter block of text.

```

376 \bool_new:N \g_scripture_red_letter_active_bool

```

(End definition for \g_scripture_red_letter_active_bool.)

__scripture_red_letter_on: Mark the beginning of a section of text attributed to Jesus Christ.

```

377 \cs_new_protected:Nn \__scripture_red_letter_on:
378 {
379     \bool_if:NT \l__scripture_red_letter_bool
380     {
381         \bool_gset_true:N \g_scripture_red_letter_active_bool
382         \exp_args:NV \color_select:n \l__scripture_red_letter_colour_tl
383         \str_if_eq:VnF \l__scripture_currenvir_str { scripture }
384         {
385             \hook_gput_next_code:nn { env / \l__scripture_currenvir_str / after }
386             {
387                 \exp_args:NV \color_select:n \l__scripture_red_letter_colour_tl
388             }
389         }
390     }
391 }

```

(End definition for __scripture_red_letter_on:.)

__scripture_red_letter_off: Mark the beginning of a section of text attributed to Jesus Christ.

```

392 \cs_new_protected:Nn \__scripture_red_letter_off:
393 {
394     \bool_if:NT \l__scripture_red_letter_bool
395     {
396         \color_select:n { scripture default colour }
397         \bool_gset_false:N \g_scripture_red_letter_active_bool
398         \str_if_eq:VnF \l__scripture_currenvir_str { scripture }
399         {
400             \hook_gput_next_code:nn { env / \l__scripture_currenvir_str / after }
401             {
402                 \color_select:n { scripture default colour }
403             }
404         }
405     }
406 }

```

(End definition for __scripture_red_letter_off:.)

3.4.3 Selecting language

__scripture_select_language: Select specified language if required.

```

407 \cs_new_protected:Nn \__scripture_select_language:
408 {
409     \tl_if_empty:NF \l__scripture_language_tl
410     {
411         \@ifpackageloaded { babel }
412         {
413             \selectlanguage { \l__scripture_language_tl }

```

```

414     }
415     {
416         \@ifpackageloaded { polyglossia }
417         {
418             \iflanguageloaded { \l__scripture_language_tl }
419             {
420                 \tl_if_empty:NTF \l__scripture_language_variant_tl
421                 {
422                     \selectlanguage { \l__scripture_language_tl }
423                 }
424                 {
425                     \selectlanguage
426                     [ variant = \l__scripture_language_variant_tl ]
427                     { \l__scripture_language_tl }
428                 }
429             }
430             {
431                 \msg_error:nnx
432                 { scripture }
433                 { language-error }
434                 { \l__scripture_language_tl }
435             }
436         }
437         {
438             \msg_warning:nnx
439                 { scripture }
440                 { language-waning }
441                 { \l__scripture_language_tl }
442             }
443         }
444     }
445 }
```

(End definition for `__scripture_select_language:..`)

3.4.4 Formatting and printing chapter numbers

`\l__scripture_chap_box` Boxes use to store and calculate drop chapter.

```

446 \box_new:N \l__scripture_chap_box
447 \box_new:N \l__scripture_chap_tmp_box
```

(End definition for `\l__scripture_chap_box` and `\l__scripture_chap_tmp_box`.)

`\l__scripture_chap_fontsize_dim` Calculated font size of a drop chapter number.

```
448 \dim_new:N \l__scripture_chap_fontsize_dim
```

(End definition for `\l__scripture_chap_fontsize_dim`.)

`\l__scripture_chap_height_dim` Calculated height of a drop chapter number.

```
449 \dim_new:N \l__scripture_chap_height_dim
```

(End definition for `\l__scripture_chap_height_dim`.)

`\l__scripture_chap_width_dim` Calculated width of drop chapter number.

```
450 \dim_new:N \l__scripture_chap_width_dim
```

(End definition for `\l_scripture_chap_width_dim`.)

`\g_scripture_chap_par_prevgraf_int` Store the number of lines a chapter paragraph takes up.

451 `\int_new:N \g_scripture_chap_par_prevgraf_int`

(End definition for `\g_scripture_chap_par_prevgraf_int`.)

`\l_scripture_chap_X_height_dim` Calculated height of X at current font size. This is used as the height for a drop chapter.

452 `\dim_new:N \l_scripture_chap_X_height_dim`

(End definition for `\l_scripture_chap_X_height_dim`.)

`__scripture_drop_chap_set_up:n` Set up chapter drop cap and calculate its various dimensions.

453 `\cs_new_protected:Nn __scripture_drop_chap_set_up:n`
454 {

455 `\cs_gset_nopar:Npn \scripturecurrentchapter { #1 }`

456 `\cs_gset_nopar:Npn \scripturecurrentverse { 1 }`

457 `\hbox_set:Nn \l_scripture_chap_tmp_box { X }`

458 `\dim_set:Nn \l_scripture_chap_X_height_dim`

459 `{ \box_ht:N \l_scripture_chap_tmp_box }`

460 `\dim_set:Nn \l_scripture_chap_height_dim`

461 `{ \baselineskip + \l_scripture_chap_X_height_dim }`

462 `\dim_set:Nn \l_scripture_chap_fontsize_dim`

463 {

464 `\f@size pt *`

465 `\dim_ratio:nn`

466 `{ \l_scripture_chap_height_dim }`

467 `{ \l_scripture_chap_X_height_dim }`

468 }

469 `\hbox_set:Nn \l_scripture_chap_tmp_box`

470 {

471 `\l_scripture_chap_font_tl`

472 `\fontsize`

473 `{ \l_scripture_chap_fontsize_dim }`

474 `{ \l_scripture_chap_fontsize_dim }`

475 `\selectfont`

476 `\str_if_eq:VnF \l_scripture_chapter_colour_tl { . }`

477 `{ \exp_args:NV \color_select:n \l_scripture_chapter_colour_tl }`

478 `__scripture_chap_format:n { #1 }`

479 }

480 `\dim_set:Nn \l_scripture_chap_width_dim`

481 `{ \box_wd:N \l_scripture_chap_tmp_box }`

Avoid breaks in the middle of drop chapters.

482 `\int_set_eq:NN \l_scripture_clubpenalty_saved_int \clubpenalty`

483 `\clubpenalty 10000`

484 `\hook_gput_next_code:nn { para / after }`

485 {

486 `\int_gset_eq:NN \g_scripture_chap_par_prevgraf_int \prevgraf`

487 `\int_compare:nNnT`

488 `\g_scripture_chap_par_prevgraf_int = 1`

489 `{ \penalty 10000 }`

490 `\hook_gput_next_code:nn { para / before }`

491 `{ \int_set_eq:NN \clubpenalty \l_scripture_clubpenalty_saved_int }`

492 }

493 }

(End definition for `_scripture_drop_chap_set_up:n`.)

`_scripture_drop_chap_output:` Output a drop chapter.

```
494 \cs_new_protected:Nn \_scripture_drop_chap_output:
  {
    \noindent
    \parshape 3 ~
      \dim_eval:n
        { \totallmargin + \l_scripture_chap_width_dim + \l_scripture_chap_sep_tl } ~
    \dim_eval:n
      { \linewidth - \l_scripture_chap_width_dim - \l_scripture_chap_sep_tl } ~
    \dim_eval:n
      { \totallmargin + \l_scripture_chap_width_dim + \l_scripture_chap_sep_tl } ~
    \dim_eval:n
      { \linewidth - \l_scripture_chap_width_dim - \l_scripture_chap_sep_tl } ~
    \dim_eval:n
      { \totallmargin ~
        \linewidth
      }
    \group_begin:
    \hook_use:n { scripture / chap / before }
    \box_use:N \l_scripture_chap_box
    \hook_use:n { scripture / chap / after }
    \group_end:
    \bool_if:NT \l_scripture_chap_show_verse_bool
      {
        \_scripture_verse_output:n { 1 }
      }
  }
```

(End definition for `_scripture_drop_chap_output:..`)

`_scripture_nodrop_chap:n` Format a non-drop chapter.

```
518 \cs_new_protected:Nn \_scripture_nodrop_chap:n
  {
    \cs_gset_nopar:Npn \scripturecurrentchapter { #1 }
    \cs_gset_nopar:Npn \scripturecurrentverse { 1 }
    \group_begin:
    \bool_if:NTF \l_scripture_chap_show_bool
      {
        \hook_use:n { scripture / chap / before }
        \group_begin:
        \str_if_eq:VnF \l_scripture_chapter_colour_tl { . }
          { \exp_args:NV \color_select:n \l_scripture_chapter_colour_tl }
        \l_scripture_chap_font_tl
        \_scripture_chap_format:n { #1 }
        \group_end:
        \skip_horizontal:N \l_scripture_chap_sep_tl
        \hook_use:n { scripture / chap / after }
        \bool_if:NT \l_scripture_chap_show_verse_bool
          {
            \_scripture_verse_output:n { 1 }
          }
      }
    \{
      \hook_use:n { scripture / chap / before }
```

```

541         \hook_use:n { scripture / chap / after }
542         \vs { 1 }
543     }
544   \group_end:
545 }
```

(End definition for `_scripture_nodrop_chap:n`.)

`_scripture_chap:n` Position a drop chapter.

```

546 \cs_new_protected:Nn \_scripture_chap:n
547 {
548   \_scripture_drop_chap_set_up:n { #1 }
549   \hbox_set:Nn \l__scripture_chap_box
550   {
551     \box_move_down:nn
552     { \baselineskip }
553     {
554       \hbox_overlap_left:n
555       {
556         \box_use:N \l__scripture_chap_tmp_box
557         \skip_horizontal:N \l__scripture_chap_sep_tl
558       }
559     }
560   }
561   \box_set_ht:Nn \l__scripture_chap_box { \c_zero_dim }
562   \box_set_dp:Nn \l__scripture_chap_box { \c_zero_dim }
563   \bool_if:NTF \l__scripture_mid_para_chap_bool
564   { \_scripture_mid_para_drop_chap_output: }
565   {
566     \par
567     \_scripture_drop_chap_output:
568   }
569   \hook_gput_next_code:nn { para / before }
570   {
571     \int_compare:nNnT
572     \g__scripture_chap_par_prevgraf_int = 1
573     { \extraskip }
574     \int_gzero:N \g__scripture_chap_par_prevgraf_int
575     \int_compare:nNnT
576     { \listdepth > \c_zero_int
577       { \parshape 1 ~ \totalleftmargin ~ \linewidth }
578     }
579   }
}
```

(End definition for `_scripture_chap:n`.)

3.4.5 Formatting and printing verse numbers

`\l__scripture_verse_par_start_bool` Flag for whether the current verse is at the start of a paragraph.

```
580 \bool_new:N \l__scripture_verse_par_start_bool
```

(End definition for `\l__scripture_verse_par_start_bool`.)

`\l__scripture_no_verse_first_bool` Suppress the next verse from formatting differently if it begins a new paragraph.

```
581 \bool_new:N \l__scripture_no_verse_first_bool
```

(End definition for `\l_scripture_no_verse_first_bool`.)

```
\__scripture_verse_output:n Output a formatted verse.  
582 \cs_new_protected:Nn \__scripture_verse_output:n  
583 {  
584     \cs_gset_nopar:Npn \scripturecurrentverse { #1 }  
585     \legacy_if:nTF { @endpe }  
586     { \bool_set_false:N \l_scripture_verse_par_start_bool }  
587     { \bool_set_true:N \l_scripture_verse_par_start_bool }  
588     \mode_if_vertical:TF  
589     { \mode_leave_vertical: }  
590     { \bool_set_false:N \l_scripture_verse_par_start_bool }  
591     \bool_if:NT \l_scripture_no_verse_first_bool  
592     {  
593         \bool_set_false:N \l_scripture_verse_par_start_bool  
594         \bool_set_false:N \l_scripture_no_verse_first_bool  
595     }  
596     \group_begin:  
597     \hook_use:n { scripture / verse / before }  
598     \bool_if:NT \l_scripture_verse_show_bool  
599     {  
600         \group_begin:  
601             \l_scripture_verse_font_tl  
602             \str_if_eq:VnF \l_scripture_verse_colour_tl { . }  
603             { \exp_args:NV \color_select:n \l_scripture_verse_colour_tl }  
604             \bool_lazy_all:nTF  
605             {  
606                 { \l_scripture_verse_first_bool }  
607                 { \l_scripture_verse_par_start_bool }  
608                 { \bool_not_p:n { \str_if_eq_p:Vn \l_scripture_currenvir_str { poetry } } }  
609             }  
610             {  
611                 \__scripture_verse_first_format:n { #1 }  
612                 \group_end:  
613                 \kern \l_scripture_verse_first_sep_tl  
614             }  
615             {  
616                 \__scripture_verse_format:n { #1 }  
617                 \group_end:  
618                 \kern \l_scripture_verse_sep_tl  
619             }  
620         }  
621     \hook_use:n { scripture / verse / after }  
622     \group_end:  
623 }
```

(End definition for `__scripture_verse_output:n`.)

3.4.6 Calculating the length of the final line in a paragraph

Store the length of the final line in a paragraph.

```
624 \dim_new:N \g_scripture_final_line_dim
```

(End definition for `\g_scripture_final_line_dim`.)

```

\_scripture_calc_final_line_length: Calculate the length of the final line in a paragraph.
625 \cs_new_protected:Nn \_scripture_calc_final_line_length:
626 {
627     \skip_set:Nn \abovedisplayshortskip { -\baselineskip }
628     \skip_set_eq:NN \abovedisplayskip \abovedisplayshortskip
629     \skip_zero:N \belowdisplayshortskip
630     \skip_zero:N \belowdisplayskip
631     $$%
632     \dim_compare:nNnT \predisplaysize > \c_zero_dim
633     {
634         \dim_gset:Nn \g__scripture_final_line_dim
635         { \predisplaysize - 2 em }
636     }
637     \cs_gset_nopar:Nx \_scripture_reset_spacing:
638     {
639         \dim_set:Nn \predisplaysize { \dim_use:N \predisplaysize }
640         \int_set:Nn \prevgraf { \int_use:N \prevgraf }
641     }
642     $$%
643     \_scripture_reset_spacing:
644     \dim_compare:nNnT \g__scripture_final_line_dim > \linewidth
645     {
646         \dim_gset_eq:NN \g__scripture_final_line_dim \linewidth
647     }
648     \dim_compare:nNnT \g__scripture_final_line_dim > { \c_zero_dim - 1 sp }
649     {
650         \skip_vertical:n { -\baselineskip - \parskip }
651     }
652 }

```

(End definition for `_scripture_calc_final_line_length`.)

3.4.7 The scripture environment

Store the current `scripture` environment.

```
653 \str_new:N \l__scripture_currenvir_str
```

(End definition for `\l__scripture_currenvir_str`.)

Correction to ensure consistent `\parskip` at start of `scripture` environment with non-zero `parskip` option.

```
654 \skip_new:N \l__scripture_parskip_correction_skip
```

(End definition for `\l__scripture_parskip_correction_skip`.)

`\g__scripture_start_bool` Flag indicating whether we are currently setting the first paragraph in a `scripture` environment. If this is true, any `aboveskip` for an inner environment will be ignored.

```
655 \bool_new:N \g__scripture_start_bool
```

(End definition for `\g__scripture_start_bool`.)

```

\__scripture_begin:n Begin a scripture quotation.
656 \cs_new_protected:Nn \__scripture_begin:n
657 {
658     \bool_if:NT \l__scripture_active_bool
659     {
660         \msg_error:nn { scripture } { nested-environment }
661     }
662     \bool_set_true:N \l__scripture_active_bool
663     \tl_set:Nn \l__scripture_currenvir_str { scripture }
664     \tl_if_no_value:nF { #1 }
665     {
666         \keys_set:nn { scripture } { #1 }
667     }
668     \__scripture_select_language:

```

If the `scripture` environment begins immediately after an `\item`, then insert a new paragraph and apply a negative skip. Life is much easier if all paragraphs in a `scripture` are the same rather than the first one being in the first paragraph of an `\item`.

```

669 \legacy_if:nT { @newlist }
670 {
671     \strut
672     \par
673     \vspace* { \dim_eval:n { -\baselineskip - \parskip } }
674 }
675 \mode_if_vertical:T
676 {
677     \addvspace { \l__scripture_aboveskip_tl }
678 }
679 \DeclareDocumentCommand { \ch } { sm }
680 {
681     \bool_if:NTF \l__scripture_chap_show_bool
682     {
683         \bool_if:NTF \l__scripture_chap_drop_bool
684         {
685             \__scripture_chap:n { ##2 }
686             \bool_if:nT { ##1 }
687             {
688                 \hook_gput_next_code:nn { para / after }
689                 { \int_gzero:N \g__scripture_chap_par_prevgraf_int }
690             }
691         }
692         { \__scripture_nodrop_chap:n { ##2 } }
693     }
694     { \__scripture_nodrop_chap:n { ##2 } }
695 }

```

Empty `\everydisplay` to ensure it isn't interfering with spacing.

```

696 \everydisplay { }
697 \int_set:Nn \predisplaypenalty { 10000 }
698 \int_set_eq:NN \postdisplaypenalty \lowpenalty
699 \bool_gset_true:N \g__scripture_start_bool
700 \bool_gset_false:N \g__scripture_poetry_end_bool
701 \dim_set_eq:NN \parindent \l__scripture_parindent_tl
702 \cs_set_eq:NN \extraskip \__scripture_extra_skip:

```

```

703 \cs_set_eq:NN \redletteron \__scripture_red_letter_on:
704 \cs_set_eq:NN \redletteroff \__scripture_red_letter_off:
705 \cs_set_eq:NN \vs \__scripture_verse_output:n
706 \cs_set_protected_nopar:Npn \added ##1
707 {
708     \group_begin:
709     \l__scripture_added_font_tl
710     \__scripture_added_format:n { ##1 }
711     \group_end:
712 }
713 \cs_set_protected_nopar:Npn \name ##1
714 {
715     \group_begin:
716     \l__scripture_name_font_tl
717     \__scripture_name_format:n { ##1 }
718     \group_end:
719 }
720 \cs_set_protected_nopar:Npn \nofirstverse
721 {
722     \bool_set_true:N \l__scripture_no_verse_first_bool
723 }
724 \cs_set_protected_nopar:Npn \LORD
725 {
726     \name { Lord }
727 }
728 \cs_set_protected_nopar:Npn \GOD
729 {
730     \name { God }
731 }
732 \cs_set_protected_nopar:Npn \textright ##1
733 {
734     \__scripture_text_right:nn { \l__scripture_text_right_sep_tl } { ##1 }
735 }
736 \hook_gclear_next_code:n { para / before }
737 \skip_set:Nn \l__scripture_parskip_correction_skip { \parskip - \l__scripture_parskip_tl }
738 \mode_if_vertical:T
739 {
740     \addvspace { \l__scripture_parskip_correction_skip }
741 }
742 \skip_set_eq:NN \parskip \l__scripture_parskip_tl
743 \l__scripture_font_tl
744 \exp_args:NnV \color_set:nn { scripture default colour } \l__scripture_colour_tl
745 \str_if_eq:VnF \l__scripture_colour_tl { . }
746 {
747     \color_select:n { scripture default colour }
748 }

```

For left and right margins, use `\parshape` is already in a list, otherwise use `\leftskip` and `\rightskip`

```

749 \bool_lazy_or:nnT
750 { \dim_compare_p:n { \l__scripture_leftmargin_tl > 0pt } }
751 { \dim_compare_p:n { \l__scripture_rightmargin_tl > 0pt } }
752 {
753     \dim_sub:Nn \linewidth

```

```

754     { \l__scripture_leftmargin_t1 + \l__scripture_rightmargin_t1 }
755     \int_compare:nNnTF
756     @listdepth > \c_zero_int
757     {
758         \dim_add:Nn \@totalleftmargin \l__scripture_leftmargin_t1
759         \parshape 1 ~ \@totalleftmargin ~ \linewidth
760     }
761     {
762         \dim_add:Nn \leftskip \l__scripture_leftmargin_t1
763         \dim_add:Nn \rightskip \l__scripture_rightmargin_t1
764     }
765 }
766 \bool_if:NF \l__scripture_indent_bool
767 {
768     \hook_gput_next_code:nn { para / begin }
769     {
770         \bool_lazy_any:nT
771         {
772             { \str_if_eq_p:Vn \l__scripture_currenvir_str { midparachap } }
773             { \str_if_eq_p:Vn \l__scripture_currenvir_str { narrow } }
774             { \str_if_eq_p:Vn \l__scripture_currenvir_str { scripture } }
775         }
776         { \para omit indent: }
777     }
778 }
779 \bool_if:NT \l__scripture_inline_bool
780     { \l__scripture_inline_begin_t1 }
781 }

```

(End definition for `__scripture_begin:n`.)

`__scripture_end:n` End a scripture quotation with a reference.

```

782 \cs_new_protected:Nn \__scripture_end:n
783 {
784     \tl_if_eq:NnTF \l__scripture_ref_align_t1 { inline }
785     {
786         \bool_lazy_or:nnF
787         { \tl_if_novalue_p:n { #1 } }
788         { \tl_if_empty_p:n { #1 } }
789         {
790             \unskip
791             \__scripture_red_letter_off:
792             \bool_if:NT \l__scripture_inline_bool
793                 { \l__scripture_inline_end_t1 }
794             \skip_horizontal:N \l__scripture_ref_sep_t1
795             \__scripture_format_full_ref:n { #1 }
796         }
797     }
798 }

```

Normally `\unskip` does not work in vertical mode, but there are some situations where it does work. The following condition is true if the `scripture` environment has ended with one of its internal environments. This removes any unwanted `belowskip` if present and leaves the previously calculated line length of the final paragraph intact.

```

799     \mode_if_vertical:TF
800     {
801         \unskip
802         \unskip
803     }
804     {
805         \tl_if_novalue:nTF { #1 }
806             { \int_zero:N \postdisplaypenalty }
807             { \int_set_eq:NN \postdisplaypenalty \highpenalty }
808         \__scripture_calc_final_line_length:
809     }

```

Restore left margin by resetting the `\parshape` if in a list based environment, otherwise the space required for the reference is incorrectly calculated.

```

810     \bool_lazy_or:nnTF
811         { \dim_compare_p:n { \l__scripture_leftmargin_tl > 0pt } }
812         { \dim_compare_p:n { \l__scripture_rightmargin_tl > 0pt } }
813     {
814         \dim_add:Nn \linewidth \l__scripture_leftmargin_tl
815         \int_compare:nNnT
816             \clistdepth > \c_zero_int
817             {
818                 \dim_sub:Nn \totallmargin \l__scripture_leftmargin_tl
819                 \parshape 1 ~ \totallmargin ~ \linewidth
820             }
821         }
822         { \parshape 1 ~ \totallmargin ~ \linewidth }
823     \__scripture_red_letter_off:
824     \bool_lazy_or:nnF
825         { \tl_if_novalue_p:n { #1 } }
826         { \tl_if_empty_p:n { #1 } }
827         { \__scripture_reference:n { #1 } }
828     \par

```

Restore right margin by resetting the `\parshape` if in a L^AT_EX list based environment, since only the left margin was restored above.

```

829     \bool_lazy_or:nnT
830         { \dim_compare_p:n { \l__scripture_leftmargin_tl > 0pt } }
831         { \dim_compare_p:n { \l__scripture_rightmargin_tl > 0pt } }
832     {
833         \int_compare:nNnT
834             \clistdepth > \c_zero_int
835             {
836                 \dim_add:Nn \linewidth \l__scripture_rightmargin_tl
837                 \parshape 1 ~ \totallmargin ~ \linewidth
838             }
839         }
840     \dim_compare:nNnTF
841         { \glueexpr \l__scripture_bellowskip_tl } > \parskip
842     {
843         \addvspace
844         {
845             \skip_eval:n { \l__scripture_bellowskip_tl - \parskip }
846         }
847     }

```

```

848     {
849         \addvspace { \l__scripture_bellowskip_t1 }
850     }
851 }
852 }
```

(End definition for `__scripture_end:n`.)

3.5 Scripture internal environments

`\l__scripture_delta_below_skip`

Correction to `\@topsepadd` for internal environments. This enables a different `aboveskip` and `bellowskip` which are normally the same for L^AT_EX lists.

```
853 \skip_new:N \l__scripture_delta_below_skip
```

(End definition for `\l__scripture_delta_below_skip`.)

3.5.1 The center environment

`__scripture_center_begin:n`

Begin a centred section in a scripture quotation.

```

854 \cs_new_protected:Nn \__scripture_center_begin:n
855 {
856     \bool_if:NT \l__scripture_active_inner_bool
857     {
858         \msg_error:nn { scripture } { nested-environment }
859     }
860     \bool_set_true:N \l__scripture_active_inner_bool
861     \tl_set:Nn \l__scripture_currenvir_str { center }
862     \tl_if_no_value:nF { #1 }
863     {
864         \keys_set:nn
865         { scripture / center }
866         { #1 }
867     }
868     \mode_if_horizontal:T
869     {
870         \par
871     }
872     \list { }
873     {
874         \skip_set_eq:NN \l__scripture_delta_below_skip \l__scripture_center_bellowskip_t1
875     }
876 }
```

Ignore `aboveskip` if at the beginning of a `scripture` environment.

```

877     \bool_if:NTF \g__scripture_start_bool
878     {
879         \skip_zero:N \topsep
880         \skip_sub:Nn \topsep \parskip
881         \skip_add:Nn \l__scripture_delta_below_skip \parskip
882         \bool_gset_false:N \g__scripture_start_bool
883     }
884     {
885         \dim_compare:nTF
886         { \parskip >= \glueexpr \l__scripture_center_aboveskip_t1 > \c_zero_skip }
887         {
888             \skip_zero:N \topsep
889             \skip_zero:N \l__scripture_delta_below_skip
890         }
891     }
892 }
```

```

887     {
888         \skip_set_eq:NN \topsep \l__scripture_center_aboveskip_tl
889         \skip_sub:Nn \l__scripture_delta_below_skip \l__scripture_center_aboveskip_t
890     }
891     \int_compare:nNnT \g__scripture_chap_par_prevgraf_int = 1
892         { \addvspace { \baselineskip } }
893         \int_gzero:N \g__scripture_chap_par_prevgraf_int
894     }
895     \skip_set_eq:NN \parsep \parskip
896     \skip_zero:N \partopsep
897     \dim_zero:N \leftmargin
898     \dim_zero:N \labelsep
899 }
900 \centering
901 \item
902 \relax
903 }

```

(End definition for `__scripture_center_begin:n`.)

`__scripture_center_end:` End a centred section in a scripture quotation.

```

904 \cs_new_protected:Nn \__scripture_center_end:
905 {
906     \__scripture_calc_final_line_length:
907     \skip_add:Nn \@topsepadd \l__scripture_delta_below_skip
908     \int_set_eq:NN \@endparpenalty \@lowpenalty
909     \endlist
910 }

```

(End definition for `__scripture_center_end:.`)

3.5.2 The `flushright` environment

`__scripture_flushright_begin:n` Begin a flushright section in a scripture quotation.

```

911 \cs_new_protected:Nn \__scripture_flushright_begin:n
912 {
913     \bool_if:NT \l__scripture_active_inner_bool
914     {
915         \msg_error:nn { scripture } { nested-environment }
916     }
917     \bool_set_true:N \l__scripture_active_inner_bool
918     \tl_set:Nn \l__scripture_currenvir_str { flushright }
919     \tl_if_novalue:nF { #1 }
920     {
921         \keys_set:nn
922             { scripture / flushright }
923             { #1 }
924     }
925     \mode_if_horizontal:T
926         { \par }
927     \list {}
928     {
929         \skip_set_eq:NN \l__scripture_delta_below_skip \l__scripture_flushright_bellowskip_tl

```

Ignore aboveskip if at the beginning of a scripture environment.

```
930          \bool_if:NTF \g__scripture_start_bool
931          {
932              \skip_zero:N \topsep
933              \skip_sub:Nn \topsep \parskip
934              \skip_add:Nn \l__scripture_delta_below_skip \parskip
935              \bool_gset_false:N \g__scripture_start_bool
936          }
937          {
938              \dim_compare:nTF
939              { \parskip >= \glueexpr \l__scripture_flushright_aboveskip_tl > \c_zero_skip }
940              {
941                  \skip_zero:N \topsep
942                  \skip_zero:N \l__scripture_delta_below_skip
943              }
944              {
945                  \skip_set_eq:NN \topsep \l__scripture_flushright_aboveskip_tl
946                  \skip_sub:Nn \l__scripture_delta_below_skip \l__scripture_flushright_aboveskip_tl
947              }
948              \int_compare:nNnT \g__scripture_chap_par_prevgraf_int = 1
949              { \addvspace { \baselineskip } }
950              \int_gzero:N \g__scripture_chap_par_prevgraf_int
951          }
952          \dim_set_eq:NN \leftmargin \l__scripture_flushright_leftmargin_tl
953          \dim_set_eq:NN \rightmargin \l__scripture_flushright_rightmargin_tl
954          \skip_set_eq:NN \parsep \parskip
955          \skip_zero:N \partopsep
956          \dim_zero:N \leftmargin
957          \dim_zero:N \labelsep
958      }
959      \raggedleft
960      \item
961      \relax
962  }
```

(End definition for `__scripture_flushright_begin:n`.)

`__scripture_flushright_end:` End a flushright section in a scripture quotation.

```
963 \cs_new_protected:Nn \__scripture_flushright_end:
964 {
965     \__scripture_calc_final_line_length:
966     \skip_add:Nn \@topsepadd \l__scripture_delta_below_skip
967     \int_set_eq:NN \@endparpenalty \@lowpenalty
968     \endlist
969 }
```

(End definition for `__scripture_flushright_end:..`)

3.5.3 The hanging environment

Save the `\parindent` for later use in `hanging` environment.

```
970 \dim_new:N \l__scripture_hanging_parindent_saved_dim
```

(End definition for `\l__scripture_hanging_parindent_saved_dim`.)

```

\__scripture_hanging_chap:n Position a drop chapter in a hanging environment.
971 \cs_new_protected:Nn \__scripture_hanging_chap:n
972 {
973     \__scripture_drop_chap_set_up:n { #1 }
974     \dim_compare:nNnTF
975         \l__scripture_chap_width_dim < \leftmargin
976     {
977         \tl_set:Nx \l__scripture_chap_sep_tl
978         {
979             \dim_eval:n { \leftmargin - \l__scripture_chap_width_dim }
980         }
981     }
982     {
983         \parshape 3 ~
984         \dim_eval:n
985         {
986             \totallmargin - \leftmargin + \l__scripture_chap_width_dim +
987             \l__scripture_chap_sep_tl
988         } ~
989         \dim_eval:n
990         {
991             \totallmargin - \leftmargin + \l__scripture_chap_width_dim -
992             \l__scripture_chap_sep_tl
993         } ~
994         \dim_eval:n
995         {
996             \totallmargin - \leftmargin + \l__scripture_chap_width_dim +
997             \l__scripture_chap_sep_tl
998         } ~
999         \dim_eval:n
1000         {
1001             \totallmargin - \leftmargin + \l__scripture_chap_width_dim -
1002             \l__scripture_chap_sep_tl
1003         } ~
1004         \totallmargin ~ \ linewidth
1005     }
1006 \mode_if_vertical:T
1007 {
1008     \tl_set:Nx \l__scripture_chap_sep_tl
1009     {
1010         \dim_eval:n
1011         {
1012             \l__scripture_chap_sep_tl + \l__scripture_hanging_parindent_saved_dim
1013         }
1014     }
1015     \__scripture_nohang:
1016 }
1017 \hbox_set:Nn \l__scripture_chap_box
1018 {
1019     \box_move_down:nn
1020     { \baselineskip }
1021     {
1022         \hbox_overlap_left:n
1023         {

```

```

1024         \box_use:N \l__scripture_chap_tmp_box
1025         \skip_horizontal:N \l__scripture_chap_sep_tl
1026     }
1027 }
1028 }
1029 \box_set_ht:Nn \l__scripture_chap_box { \c_zero_dim }
1030 \box_set_dp:Nn \l__scripture_chap_box { \c_zero_dim }
1031 \group_begin:
1032 \hook_use:n { scripture / chap / before }
1033 \box_use:N \l__scripture_chap_box
1034 \hook_use:n { scripture / chap / after }
1035 \group_end:
1036 \bool_if:NT \l__scripture_chap_show_verse_bool
1037 {
1038     \__scripture_verse_output:n { 1 }
1039 }
1040 \hook_gput_next_code:nn { para / begin }
1041     { \parshape 1 ~ \totalleftmargin ~ \linewidth }
1042 }

```

(End definition for `__scripture_hanging_chap:n`.)

`__scripture_hanging_verse:n` Position a `\vs` in a `hanging` environment. The verse is set to overlap to the left if at the beginning of a hanging paragraph.

```

1043 \cs_new_protected:Nn \__scripture_hanging_verse:n
1044 {
1045     \mode_if_vertical:TF
1046     {
1047         \strut
1048         \hbox_overlap_left:n
1049         {
1050             \__scripture_verse_output:n { #1 }
1051         }
1052     }
1053     { \__scripture_verse_output:n { #1 } }
1054 }

```

(End definition for `__scripture_hanging_verse:n`.)

`__scripture_nohang:` Don't hang a paragraph in a `hanging` environment. Instead the paragraph is indented by `\parindent` from its normal hanging position.

```

1055 \cs_new_protected_nopar:Nn \__scripture_nohang:
1056 {
1057     \para_raw_noindent:
1058     \hbox_to_wd:nn { \l__scripture_hanging_parindent_saved_dim } { }
1059 }

```

(End definition for `__scripture_nohang:..`)

`__scripture_hanging_begin:n` Begin a hanging section in a scripture quotation.

```

1060 \cs_new_protected:Nn \__scripture_hanging_begin:n
1061 {
1062     \bool_if:NT \l__scripture_active_inner_bool
1063     {
1064         \msg_error:nn { scripture } { nested-environment }

```

```

1065     }
1066     \bool_set_true:N \l__scripture_active_inner_bool
1067     \tl_set:Nn \l__scripture_currenvir_str { hanging }
1068     \tl_if_no_value:nF { #1 }
1069     {
1070         \keys_set:nn
1071             { scripture / hanging }
1072             { #1 }
1073     }
1074     \mode_if_horizontal:T
1075         { \par }
1076     \list { }
1077     {
1078         \skip_set_eq:NN \l__scripture_delta_below_skip \l__scripture_hanging_bellowskip_tl

```

Ignore aboveskip if at the beginning of a `scripture` environment.

```

1079         \bool_if:NTF \g__scripture_start_bool
1080             {
1081                 \dim_zero:N \topsep
1082                 \skip_sub:Nn \topsep \parskip
1083                 \skip_add:Nn \l__scripture_delta_below_skip \parskip
1084                 \bool_gset_false:N \g__scripture_start_bool
1085             }
1086             {
1087                 \dim_compare:nTF
1088                     { \parskip } \glueexpr \l__scripture_hanging_aboveskip_tl > \c_zero_skip
1089                     {
1090                         \skip_zero:N \topsep
1091                         \skip_zero:N \l__scripture_delta_below_skip
1092                     }
1093                     {
1094                         \skip_set_eq:NN \topsep \l__scripture_hanging_aboveskip_tl
1095                         \skip_sub:Nn \l__scripture_delta_below_skip \l__scripture_hanging_aboveskip_
1096                     }
1097                     \int_compare:nNnT \g__scripture_chap_par_prevgraf_int = 1
1098                         { \addvspace { \baselineskip } }
1099                         \int_gzero:N \g__scripture_chap_par_prevgraf_int
1100                     }
1101                     \dim_set:Nn \leftmargin
1102                         { \l__scripture_hanging_leftmargin_tl + \l__scripture_hanging_hang_tl }
1103                     \dim_set_eq:NN \rightmargin \l__scripture_hanging_rightmargin_tl
1104                     \dim_set:Nn \itemindent { -\l__scripture_hanging_hang_tl }
1105                     \dim_set:Nn \listparindent { -\l__scripture_hanging_hang_tl }
1106                     \skip_set_eq:NN \parsep \parskip
1107                     \skip_zero:N \partopsep
1108                     \dim_zero:N \labelsep
1109                     \dim_set_eq:NN \l__scripture_hanging_parindent_saved_dim \parindent
1110                 }
1111             \DeclareDocumentCommand { \ch } { sm }
1112             {
1113                 \bool_if:NTF \l__scripture_chap_show_bool
1114                 {
1115                     \bool_if:NTF \l__scripture_chap_drop_bool
1116                         { \__scripture_hanging_chap:n { ##2 } }
1117                         { \__scripture_nodrop_chap:n { ##2 } }

```

```

1118         }
1119         { \__scripture_nodrop_chap:n { ##2 } }
1120     }
1121     \cs_set_eq:NN \vs \__scripture_hanging_verse:n
1122     \cs_set_eq:NN \nohang \__scripture_nohang:
1123     \item
1124     \relax
1125 }
```

(End definition for `__scripture_hanging_begin:n`.)

`__scripture_hanging_end:` End a hanging section in a scripture quotation.

```

1126 \cs_new_protected:Nn \__scripture_hanging_end:
1127 {
1128     \__scripture_calc_final_line_length:
1129     \skip_add:Nn \topsepadd \l__scripture_delta_below_skip
1130     \int_set_eq:NN \endparpenalty \lowpenalty
1131     \endlist
1132 }
```

(End definition for `__scripture_hanging_end:..`)

3.5.4 The `midparachap` environment

`__scripture_vbox_set_top:Nw` Define missing `\vbox_set_top:Nw` function.

```

1133 \cs_new_protected:Npn \__scripture_vbox_set_top:Nw #1
1134 {
1135     \tex_setbox:D #1 \tex_vtop:D
1136     \c_group_begin_token
1137     \color_group_begin:
1138 }
```

(End definition for `__scripture_vbox_set_top:Nw`.)

`\l__scripture_mid_para_chap_bool` Flag if setting a paragraph containing a mid-paragraph chapter.

```
1139 \bool_new:N \l__scripture_mid_para_chap_bool
```

(End definition for `\l__scripture_mid_para_chap_bool`.)

`\l__scripture_mid_para_chap_line_box` Store last line before a mid-paragraph chapter.

```
1140 \box_new:N \l__scripture_mid_para_chap_line_box
```

(End definition for `\l__scripture_mid_para_chap_line_box`.)

`\g__scripture_mid_para_chap_prevdepth_dim` Store the `\prevdepth` of the final paragraph in a `midparachap` environment.

```
1141 \dim_new:N \g__scripture_mid_para_chap_prevdepth_dim
```

(End definition for `\g__scripture_mid_para_chap_prevdepth_dim`.)

`\g__scripture_mid_para_chap_prevgraf_int` Store the `\prevgraf` of the final paragraph in a `midparachap` environment.

```
1142 \int_new:N \g__scripture_mid_para_chap_prevgraf_int
```

(End definition for `\g__scripture_mid_para_chap_prevgraf_int`.)

`\l__scripture_mid_para_chap_snap_box` Store unpacked last line before a mid-paragraph chapter.

```
1143 \box_new:N \l__scripture_mid_para_chap_snap_box
```

(End definition for `\l_scripture_mid_para_chap_snap_box`.)

Store space factor before a mid-paragraph chapter.

1144 `\int_new:N \l_scripture_mid_para_chap_spacefactor_int`

(End definition for `\l_scripture_mid_para_chap_spacefactor_int`.)

Boxes containing a paragraph with a chapter break and its split if needed.

1145 `\box_new:N \l_scripture_mid_para_chap_box`

1146 `\box_new:N \l_scripture_mid_para_chap_split_box`

1147 `\box_new:N \l_scripture_mid_para_chap_split_top_box`

(End definition for `\l_scripture_mid_para_chap_box`, `\l_scripture_mid_para_chap_split_box`, and `\l_scripture_mid_para_chap_split_top_box`.)

`\scripture_mid_para_drop_chap_output:`

1148 `\cs_new_protected:Nn \scripture_mid_para_drop_chap_output:`

1149 `{`

1150 `\unskip`

1151 `\int_set_eq:NN \l_scripture_mid_para_chap_spacefactor_int \spacefactor`

1152 `\strut`

1153 `\par`

1154 `\box_set_to_last:N \l_scripture_mid_para_chap_line_box`

1155 `\hbox_set:Nn \l_scripture_mid_para_chap_snap_box`

1156 `{`

1157 `\hbox_unpack_drop:N \l_scripture_mid_para_chap_line_box`

1158 `\unskip`

1159 `\unskip`

1160 `\unpenalty`

1161 `}`

1162 `\nointerlineskip`

1163 `\dim_compare:nNnTF`

1164 `{`

1165 `\box_wd:N \l_scripture_mid_para_chap_snap_box +`

1166 `\l_scripture_chap_width_dim +`

1167 `\l_scripture_chap_sep_tl`

1168 `}`

1169 `<`

1170 `{ \ linewidth - \leftskip - \rightskip - 3 em }`

1171 `{`

1172 `\scripture_drop_chap_output:`

1173 `\hbox_unpack_drop:N \l_scripture_mid_para_chap_snap_box`

1174 `\int_set_eq:NN \spacefactor \l_scripture_mid_para_chap_spacefactor_int`

1175 `\c_space_tl`

1176 `\scripture_verse_output:n { 1 }`

1177 `}`

1178 `{`

1179 `\group_begin:`

1180 `\noindent`

1181 `\skip_horizontal:n { -\leftskip }`

1182 `\hbox_unpack_drop:N \l_scripture_mid_para_chap_snap_box`

1183 `\skip_zero:N \parfillskip`

1184 `\par`

1185 `\group_end:`

```

1186     \_scripture_drop_chap_output:
1187     \bool_if:NT \l__scripture_midparachap_show_verse_bool
1188     {
1189         \_scripture_verse_output:n { 1 }
1190     }
1191 }
1192 }
```

(End definition for `_scripture_mid_para_drop_chap_output`.)

`_scripture_mid_para_chap_begin:n` Begin a paragraph containing a mid-paragraph chapter.

```

1193 \cs_new_protected:Nn \_scripture_mid_para_chap_begin:n
1194 {
1195     \tl_set:Nn \l__scripture_currenvir_str { midparachap }
1196     \tl_if_no_value:nF { #1 }
1197     {
1198         \keys_set:nn
1199         { scripture / midparachap }
1200         { #1 }
1201     }
1202     \bool_lazy_and:nnt
1203     { \bool_if_p:n \l__scripture_chap_show_verse_bool }
1204     { \bool_if_p:n \l__scripture_chap_drop_bool }
1205     {
1206         \bool_set_true:N \l__scripture_midparachap_show_verse_bool
1207         \bool_set_false:N \l__scripture_chap_show_verse_bool
1208     }
1209     \par
1210     \bool_set_true:N \l__scripture_mid_para_chap_bool
1211     \_scripture_vbox_set_top:Nw \l__scripture_mid_para_chap_box
1212     \skip_zero:N \parskip
1213 }
```

(End definition for `_scripture_mid_para_chap_begin:n`.)

`_scripture_mid_para_chap_end:` End a paragraph containing a mid-paragraph chapter.

```

1214 \cs_new_protected:Nn \_scripture_mid_para_chap_end:
1215 {
1216     \par
1217     \int_gset_eq:NN \g__scripture_mid_para_chap_prevgraf_int \prevgraf
1218     \dim_gset_eq:NN \g__scripture_mid_para_chap_prevdepth_dim \prevdepth
1219     \box_set_to_last:N \l__scripture_mid_para_chap_line_box
1220     \hbox_set:Nn \l__scripture_mid_para_chap_snap_box
1221     {
1222         \hbox_unpack:N \l__scripture_mid_para_chap_line_box
1223         \unskip
1224         \unskip
1225         \unpenalty
1226     }
1227     \dim_gset:Nn \g__scripture_final_line_dim { \box_wd:N \l__scripture_mid_para_chap_snap_b
1228     \box_clear:N \l__scripture_mid_para_chap_snap_box
1229     \nointerlineskip
1230     \int_compare:nNnT
1231         \prevgraf < 3
1232     {
```

```

1233     \noindent
1234     \skip_horizontal:n { \l__scripture_chap_width_dim + \l__scripture_chap_sep_tl }
1235     \dim_gadd:Nn \g__scripture_final_line_dim { \l__scripture_chap_width_dim + \l__scripture_chap_sep_tl }
1236   }
1237   \box_use_drop:N \l__scripture_mid_para_chap_line_box
1238   \vbox_set_end:

```

Attempt to allow the mid-paragraph chapter box to break across pages.

```

1239   \mode_if_inner:TF
1240   {
1241     \noindent
1242     \box_use_drop:N \l__scripture_mid_para_chap_box
1243   }
1244   {
1245     \dim_compare:nNnTF
1246       { \box_ht_plus_dp:N \l__scripture_mid_para_chap_box }
1247     >
1248     { \pagegoal - \pagetotal - \baselineskip }
1249     {
1250       \int_set:Nn \vbadness { 10000 }
1251       \vbox_set_split_to_ht:NNn
1252         \l__scripture_mid_para_chap_split_box \l__scripture_mid_para_chap_box
1253         { \pagegoal - \pagetotal - \baselineskip }
1254       \vbox_set_top:Nn \l__scripture_mid_para_chap_split_top_box
1255         { \vbox_unpack_drop:N \l__scripture_mid_para_chap_split_box }
1256       \noindent
1257       \box_use_drop:N \l__scripture_mid_para_chap_split_top_box
1258       \goodbreak
1259       \box_use_drop:N \l__scripture_mid_para_chap_box
1260     }
1261     {
1262       \noindent
1263       \box_use_drop:N \l__scripture_mid_para_chap_box
1264     }
1265   }
1266   \par
1267   \dim_set_eq:NN \prevdepth \g__scripture_mid_para_chap_prevdepth_dim
1268   \int_zero:N \prevgraf
1269   \skip_vertical:n { -\parskip - \baselineskip }
1270   \noindent
1271   \skip_horizontal:N \g__scripture_final_line_dim
1272   \int_gset_eq:NN \g__scripture_chap_par_prevgraf_int \g__scripture_mid_para_chap_prevgraf_int
1273   \hook_gput_next_code:nn { para / before }
1274   {
1275     \int_gzero:N \g__scripture_chap_par_prevgraf_int
1276     \int_compare:nNnT
1277       { \listdepth > \c_zero_int
1278         { \parshape 1 ~ \totallleftmargin ~ \linewidth }
1279       }
1280   }

```

(End definition for `__scripture_mid_para_chap_end:..`)

3.5.5 The narrow environment

```
\__scripture_narrow_begin:n Begin a narrow section in a scripture quotation.
1281 \cs_new_protected:Nn \__scripture_narrow_begin:n
1282 {
1283     \bool_if:NT \l__scripture_active_inner_bool
1284     {
1285         \msg_error:nn { scripture } { nested-environment }
1286     }
1287     \bool_set_true:N \l__scripture_active_inner_bool
1288     \tl_set:Nn \l__scripture_currenvir_str { narrow }
1289     \tl_if_no_value:nF { #1 }
1290     {
1291         \keys_set:nn
1292             { scripture / narrow }
1293             { #1 }
1294     }
1295     \mode_if_horizontal:T
1296     {
1297         \par
1298     }
1299     \list { }
1300     {
1301         \skip_set_eq:NN \l__scripture_delta_below_skip \l__scripture_narrow_bellowskip_tl
1302         \g__scripture_start_bool
1303         {
1304             \skip_zero:N \topsep
1305             \skip_sub:Nn \topsep \parskip
1306             \skip_add:Nn \l__scripture_delta_below_skip \parskip
1307             \bool_gset_false:N \g__scripture_start_bool
1308         }
1309         {
1310             \dim_compare:nTF
1311                 { \parskip >= \glueexpr \l__scripture_narrow_aboveskip_tl > \c_zero_skip }
1312                 {
1313                     \skip_zero:N \topsep
1314                     \skip_zero:N \l__scripture_delta_below_skip
1315                 }
1316                 {
1317                     \skip_set_eq:NN \topsep \l__scripture_narrow_aboveskip_tl
1318                     \skip_sub:Nn \l__scripture_delta_below_skip \l__scripture_narrow_aboveskip_t
1319                 }
1320                 \int_compare:nNnT \g__scripture_chap_par_prevgraf_int = 1
1321                 {
1322                     \addvspace { \baselineskip }
1323                     \int_gzero:N \g__scripture_chap_par_prevgraf_int
1324                 }
1325                 \dim_set_eq:NN \leftmargin \l__scripture_narrow_leftmargin_t
1326                 \dim_set_eq:NN \rightmargin \l__scripture_narrow_rightmargin_t
1327                 \dim_set_eq:NN \listparindent \parindent
1328                 \dim_set_eq:NN \itemindent \parindent
1329                 \skip_set_eq:NN \parsep \parskip
1330                 \skip_zero:N \partopsep
1331                 \dim_zero:N \labelsep
1332             }
1333             \item
```

```

1331     \relax
1332 }

```

(End definition for `_scripture_narrow_begin:n.`)

`_scripture_narrow_end:` End a narrow section in a scripture quotation.

```

1333 \cs_new_protected:Nn \_scripture_narrow_end:
1334 {
1335     \_scripture_calc_final_line_length:
1336     \skip_add:Nn \topsepadd \l_scripture_delta_below_skip
1337     \int_set_eq:NN \endparpenalty \lowpenalty
1338     \endlist
1339 }

```

(End definition for `_scripture_narrow_end:.`)

3.5.6 The poetry environment

<code>scripture/poetry/para/after</code>	This hook is an internal hook used to adjust the <code>\parshape</code> within a <code>poetry</code> environment after drop chapter numbers.
	<pre>1340 \hook_new:n { scripture / poetry / para / after }</pre>
	(End definition for <code>scripture/poetry/para/after</code> . This variable is documented on page ??.)
<code>\g_scripture_poetry_end_bool</code>	Flag indicating that a <code>poetry</code> environment just ended.
	<pre>1341 \bool_new:N \g_scripture_poetry_end_bool</pre>
	(End definition for <code>\g_scripture_poetry_end_bool</code> .)
<code>scripture_poetry_midparachap_show_verse_bool</code>	Flag indicating whether the verse number should be printed immediately after a <code>\ch</code> or not in a <code>poetry</code> environment.
	<pre>1342 \bool_new:N \g_scripture_poetry_midparachap_show_verse_bool</pre>
	(End definition for <code>\g_scripture_poetry_midparachap_show_verse_bool</code> .)
<code>\l_scripture_poetry_chap_indent_dim</code> <code>\l_scripture_poetry_chap_sep_dim</code>	Store calculated indent and sep when a drop chapter appears in a <code>poetry</code> environment.
	<pre>1343 \dim_new:N \l_scripture_poetry_chap_indent_dim 1344 \dim_new:N \l_scripture_poetry_chap_sep_dim</pre>
	(End definition for <code>\l_scripture_poetry_chap_indent_dim</code> and <code>\l_scripture_poetry_chap_sep_dim</code> .)
<code>scripture_poetry_chap_parshape_correction_dim</code>	Correction to <code>\parshape</code> in chapter affected lines in a <code>poetry</code> environment.
	<pre>1345 \dim_new:N \l_scripture_poetry_chap_parshape_correction_dim</pre>
	(End definition for <code>\l_scripture_poetry_chap_parshape_correction_dim</code> .)
<code>\l_scripture_poetry_prevgraf_int</code>	Store the number of lines a line of poetry takes up.
	<pre>1346 \int_new:N \l_scripture_poetry_prevgraf_int</pre>
	(End definition for <code>\l_scripture_poetry_prevgraf_int</code> .)

_scripture_poetry_extra_skip: Insert a little extra vertical space between two lines in a `poetry` environment.

```

1347 \cs_new_protected:Nn \_scripture_poetry_extra_skip:
1348 {
1349     \skip_vertical:n { \l__scripture_extraskip_tl - \baselineskip - \parskip }
1350     \bool_gset_false:N \g__scripture_poetry_midparachap_show_verse_bool
1351     \strut
1352     \hook_gput_next_code:nn { para / after }
1353     {
1354         \hook_gput_next_code:nn { para / after }
1355         {
1356             \bool_gset_eq:NN
1357             \g__scripture_poetry_midparachap_show_verse_bool
1358             \l__scripture_midparachap_show_verse_bool
1359         }
1360     }
1361 }
```

(End definition for `_scripture_poetry_extra_skip:..`)

_scripture_poetry_text_right:nn Align a word to the right and finish a paragraph, pushing to the next line if there is not space for the word.

```

1362 \cs_new_protected:Nn \_scripture_poetry_text_right:nn
1363 {
1364     {
1365         \unskip
1366         \hfil
1367         \penalty 50
1368         \skip_horizontal:n { #1 }
1369         \hbox:n {}
1370         \nobreak
1371         \hfill
1372         #2
1373         \skip_zero:N \parfillskip
1374         \int_zero:N \finalhyphendemerits
1375     }
1376 }
```

(End definition for `_scripture_poetry_text_right:nn.`)

_scripture_selah_output: Output Selah at the end of a line.

```

1377 \cs_new_protected:Nn \_scripture_selah_output:
1378 {
1379     \group_begin:
1380     \l__scripture_selah_font_tl
1381     \_scripture_poetry_text_right:nn
1382     { \l__scripture_selah_sep_tl }
1383     { \_scripture_selah_format:n { \l__scripture_selah_text_tl } }
1384     \group_end:
1385 }
```

(End definition for `_scripture_selah_output:..`)

_scripture_poetry_chap:n Position a chapter in a `poetry` environment.

```

1386 \cs_new_protected:Nn \_scripture_poetry_chap:n
```

```

1387  {
1388    \__scripture_drop_chap_set_up:n { #1 }
1389    \mode_if_vertical:TF
1390    {
1391      \dim_set_eq:NN \l__scripture_poetry_chap_indent_dim \l__scripture_poetry_indent_tl
1392      \mode_leave_vertical:
1393    }
1394    { \dim_zero:N \l__scripture_poetry_chap_indent_dim }
1395    \dim_set_eq:NN \l__scripture_poetry_chap_sep_dim \l__scripture_chap_sep_tl
1396    \dim_compare:nNnT
1397      { \l__scripture_chap_width_dim + \l__scripture_chap_sep_tl }
1398      <
1399      { \l__scripture_poetry_leftmargin_tl + \l__scripture_poetry_chap_indent_dim }
1400    {
1401      \dim_set:Nn \l__scripture_poetry_chap_sep_dim
1402      {
1403        \l__scripture_poetry_leftmargin_tl + \l__scripture_poetry_chap_indent_dim -
1404        \l__scripture_chap_width_dim
1405      }
1406    }
1407    \hbox_set:Nn \l__scripture_chap_box
1408    {
1409      \box_move_down:nn
1410      { \baselineskip }
1411      {
1412        \hbox_overlap_left:n
1413        {
1414          \box_use:N \l__scripture_chap_tmp_box
1415          \skip_horizontal:N \l__scripture_poetry_chap_sep_dim
1416        }
1417      }
1418    }
1419    \box_set_ht:Nn \l__scripture_chap_box { \c_zero_dim }
1420    \box_set_dp:Nn \l__scripture_chap_box { \c_zero_dim }
1421    \dim_set:Nn \l__scripture_poetry_chap_parshape_correction_dim
1422    {
1423      \l__scripture_chap_width_dim + \l__scripture_poetry_chap_sep_dim -
1424      \l__scripture_poetry_leftmargin_tl - \l__scripture_poetry_chap_indent_dim
1425    }
1426    \parshape 2 ~
1427      \dim_eval:n
1428        { \totallleftmargin + \l__scripture_poetry_chap_parshape_correction_dim } ~
1429      \dim_eval:n
1430        { \linewidth - \l__scripture_poetry_chap_parshape_correction_dim } ~
1431      \dim_eval:n
1432        { \totallleftmargin + \l__scripture_poetry_big_indent_tl } ~
1433      \dim_eval:n
1434        { \linewidth - \l__scripture_poetry_big_indent_tl }

Because of interactions with LATEX list environments and \__scripture_obeylines:, \__scripture_poetry_par: setting the \parshape for the second line after a drop chapter number is more difficult than it should be. There's probably a better way.

1435      \dim_compare:nNnT
1436        { \l__scripture_chap_width_dim + \l__scripture_poetry_chap_sep_dim }

```

```

1437 >
1438 \l__scripture_poetry_leftmargin_tl
1439 {
1440     \hook_gput_next_code:nn { scripture / poetry / para / after }
1441     {
1442         \int_compare:nNnT \l__scripture_poetry_prevgraf_int = 1
1443         {

```

This `\parshape` is in effect when the next line is the second half of a poetry verse.

```

1444     \dim_compare:nNnTF
1445         { \l__scripture_chap_width_dim + \l__scripture_chap_sep_t1 }
1446         <
1447         { \l__scripture_poetry_leftmargin_tl + \l__scripture_poetry_indent_t1 }
1448         { \dim_zero:N \l__scripture_poetry_chap_parshape_correction_dim }
1449         {
1450             \dim_set:Nn \l__scripture_poetry_chap_parshape_correction_dim
1451             {
1452                 \l__scripture_chap_width_dim + \l__scripture_chap_sep_t1 -
1453                 \l__scripture_poetry_leftmargin_tl - \l__scripture_poetry_indent_t1
1454             }
1455         }
1456     \parshape 2 ~
1457     \dim_eval:n
1458         { \@totaleftmargin + \l__scripture_poetry_chap_parshape_correction_dim }
1459     \dim_eval:n
1460         { \linewidth - \l__scripture_poetry_chap_parshape_correction_dim } ~
1461     \dim_eval:n
1462         { \@totaleftmargin + \l__scripture_poetry_big_indent_t1 } ~
1463     \dim_eval:n
1464         { \linewidth - \l__scripture_poetry_big_indent_t1 }
1465     \hook_gput_next_code:nn { para / after }
1466     {
1467         \hook_gclear_next_code:n { scripture / poetry / para / after }
1468     }
1469     \hook_gput_next_code:nn { scripture / poetry / para / after }
1470     {

```

This `\parshape` is in effect when the next line is the first half of a poetry verse.

```

1471     \dim_compare:nNnTF
1472         { \l__scripture_chap_width_dim + \l__scripture_chap_sep_t1 }
1473         <
1474         \l__scripture_poetry_leftmargin_tl
1475         { \dim_zero:N \l__scripture_poetry_chap_parshape_correction_dim }
1476         {
1477             \dim_set:Nn \l__scripture_poetry_chap_parshape_correction_dim
1478             {
1479                 \l__scripture_chap_width_dim + \l__scripture_chap_sep_t1 -
1480                 \l__scripture_poetry_leftmargin_tl
1481             }
1482         }
1483     \parshape 2 ~
1484     \dim_eval:n
1485         { \@totaleftmargin + \l__scripture_poetry_chap_parshape_correction_dim }
1486     \dim_eval:n
1487         { \linewidth - \l__scripture_poetry_chap_parshape_correction_dim } ~

```

```

1488     \dim_eval:n
1489         { \@totalleftmargin + \l__scripture_poetry_big_indent_tl } ~
1490     \dim_eval:n
1491         { \linewidth - \l__scripture_poetry_big_indent_tl }
1492     }
1493     }
1494     }
1495     }
1496 \group_begin:
1497 \hook_use:n { scripture / chap / before }
1498 \box_use:N \l__scripture_chap_box
1499 \hook_use:n { scripture / chap / after }
1500 \group_end:
1501 \bool_lazy_or:nnT
1502     { \bool_if_p:n \l__scripture_chap_show_verse_bool }
1503     { \bool_if_p:n \g__scripture_poetry_midparachap_show_verse_bool }
1504     {
1505         \__scripture_verse_output:n { 1 }
1506     }
1507 }

```

(End definition for `__scripture_poetry_chap:n`.)

`__scripture_poetry_nodrop_chap:n` Format a non-drop chapter for poetry environment in a `scripture` quotation.

```

1508 \cs_new_protected:Nn \__scripture_poetry_nodrop_chap:n
1509     {
1510         \cs_gset_nopar:Npn \scripturecurrentchapter { #1 }
1511         \cs_gset_nopar:Npn \scripturecurrentverse { 1 }
1512         \group_begin:
1513             \bool_if:NTF \l__scripture_chap_show_bool
1514             {
1515                 \hbox_overlap_left:n
1516                 {
1517                     \hook_use:n { scripture / chap / before }
1518                     \group_begin:
1519                         \l__scripture_chap_font_tl
1520                         \str_if_eq:VnF \l__scripture_chapter_colour_tl { . }
1521                         { \exp_args:NV \color_select:n \l__scripture_chapter_colour_tl }
1522                         \__scripture_chap_format:n { #1 }
1523                     \group_end:
1524                         \skip_horizontal:N \l__scripture_chap_sep_tl
1525                         \hook_use:n { scripture / chap / after }
1526                     }
1527             \bool_lazy_or:nnT
1528                 { \bool_if_p:n \l__scripture_chap_show_verse_bool }
1529                 { \bool_if_p:n \g__scripture_poetry_midparachap_show_verse_bool }
1530                 {
1531                     \__scripture_verse_output:n { 1 }
1532                 }
1533             {
1534                 \hook_use:n { scripture / chap / before }
1535                 \hook_use:n { scripture / chap / after }
1536                 \vs { 1 }
1537             }

```

```

1538     }
1539   \group_end:
1540 }

(End definition for \__scripture_poetry_nodrop_chap:n)

\__scripture_poetry_mode_vertical_verse:n Format a verse for poetry scripture quotations in vertical and horizontal mode.
1541 \cs_new_protected:Nn \__scripture_poetry_mode_vertical_verse:n
1542 {
1543   \group_begin:
1544   \tl_set_eq:NN \l__scripture_verse_sep_tl \l__scripture_poetry_verse_sep_tl
1545   \strut
1546   \bool_if:NTF \l__scripture_poetry_verse_right_bool
1547   {
1548     \hbox_overlap_left:n
1549     {
1550       \__scripture_verse_output:n { #1 }
1551     }
1552   }
1553   {
1554     \hbox_overlap_left:n
1555     {
1556       \hbox_overlap_right:n
1557       {
1558         \__scripture_verse_output:n { #1 }
1559       }
1560       \skip_horizontal:N \l__scripture_poetry_leftmargin_tl
1561     }
1562   }
1563   \group_end:
1564 }

1565 \cs_new_protected:Nn \__scripture_poetry_mode_horizontal_verse:n
1566 {
1567   \group_begin:
1568   \tl_set_eq:NN \l__scripture_verse_sep_tl \l__scripture_poetry_verse_sep_tl
1569   \skip_horizontal:n { -\listparindent }
1570   \__scripture_poetry_mode_vertical_verse:n { #1 }
1571   \skip_horizontal:N \listparindent
1572   \group_end:
1573 }

(End definition for \__scripture_poetry_mode_vertical_verse:n)

```

__scripture_poetry_par: par macro for poetry sections

```

1574 \cs_new_protected:Nn \__scripture_poetry_par:
1575 {
1576   \mode_if_vertical:TF
1577   {
1578     \cs_set_eq:NN \vs \__scripture_poetry_mode_vertical_verse:n
1579     \noindent
1580   }
1581   {
1582     \cs_set_eq:NN \vs \__scripture_poetry_mode_horizontal_verse:n
1583     \__scripture_tmp_para_end:
1584     \int_set_eq:NN \l__scripture_poetry_prevgraf_int \prevgraf

```

```

1585     }
1586     \parshape 2 ~
1587         \G@totalleftmargin ~
1588         \linewidth ~
1589         \dim_eval:n
1590             { \G@totalleftmargin + \l__scripture_poetry_big_indent_tl } ~
1591         \dim_eval:n
1592             { \linewidth - \l__scripture_poetry_big_indent_tl }
1593         \hook_use:n { scripture / poetry / para / after }
1594     }

```

(End definition for `__scripture_poetry_par:..`)

`__scripture_obeylines:` Special version of obeylines which doesn't insert par at end of environment.

```

1595 \group_begin:
1596     \char_set_catcode_active:N \^\^M
1597     \cs_gset_protected_nopar:Nn \__scripture_obeylines: %
1598     {%
1599         \char_set_catcode_active:N \^\^M%
1600         \cs_set_eq:NN \^\^M \__scripture_obeylines_end:%
1601     }%
1602 \group_end:
1603 \cs_new_protected:Nn \__scripture_obeylines_end:
1604 {
1605     \peek_meaning:NF \end
1606     {
1607         \par
1608         \int_set:Nn \l__scripture_poetry_prevgraf_int { \int_use:N \prevgraf }
1609     }
1610 }

```

(End definition for `__scripture_obeylines:..`)

`__scripture_poetry_begin:` Begin a poetry section in a scripture quotation.

```

1611 \cs_new_protected:Nn \__scripture_poetry_begin:
1612 {
1613     \bool_if:NT \l__scripture_active_inner_bool
1614     {
1615         \msg_error:nn { scripture } { nested-environment }
1616     }
1617     \bool_set_true:N \l__scripture_active_inner_bool
1618     \tl_set:Nn \l__scripture_currenvir_str { poetry }
1619     \mode_if_horizontal:T
1620     {
1621         \par
1622     }
1623     \list {}
1624     {
1625         \skip_set_eq:NN \l__scripture_delta_below_skip \l__scripture_poetry_beforeskip_tl
1626         \bool_if:NTF \g__scripture_start_bool
1627         {
1628             \skip_zero:N \topsep
1629             \skip_sub:Nn \topsep \parskip
1630             \skip_add:Nn \l__scripture_delta_below_skip \parskip
1631             \bool_gset_false:N \g__scripture_start_bool
1632         }
1633     }

```

```

1632   \dim_compare:nTF
1633     { \parskip >= \glueexpr \l__scripture_poetry_aboveskip_tl > \c_zero_skip }
1634     {
1635       \skip_zero:N \topsep
1636       \skip_zero:N \l__scripture_delta_below_skip
1637     }
1638     {
1639       \skip_set_eq:NN \topsep \l__scripture_poetry_aboveskip_tl
1640       \skip_sub:Nn \l__scripture_delta_below_skip \l__scripture_poetry_aboveskip_t
1641     }
1642   \int_compare:nNnT \g__scripture_chap_par_prevgraf_int = 1
1643     { \addvspace { \baselineskip } }
1644     \int_gzero:N \g__scripture_chap_par_prevgraf_int
1645   }
1646   \dim_set_eq:NN \leftmargin \l__scripture_poetry_leftmargin_tl
1647   \dim_set_eq:NN \rightmargin \l__scripture_poetry_rightmargin_tl
1648   \dim_set_eq:NN \itemindent \l__scripture_poetry_indent_tl
1649   \dim_set_eq:NN \listparindent \l__scripture_poetry_indent_tl
1650   \skip_zero:N \parsep
1651   \skip_zero:N \partopsep
1652   \dim_zero:N \labelsep
1653 }
1654 \raggedright
1655 \dim_set_eq:NN \listparindent \l__scripture_poetry_indent_tl
1656 \dim_set_eq:NN \parindent \l__scripture_poetry_indent_tl
1657 \bool_gset_false:N \g__scripture_poetry_midparachap_show_verse_bool
1658 \DeclareDocumentCommand { \ch } { sm }
1659   {
1660     \bool_if:NTF \l__scripture_chap_show_bool
1661     {
1662       \bool_if:NTF \l__scripture_chap_drop_bool
1663         { \__scripture_poetry_chap:n { ##2 } }
1664         { \__scripture_poetry_nodrop_chap:n { ##2 } }
1665     }
1666     { \__scripture_poetry_nodrop_chap:n { ##2 } }
1667   }
1668 \cs_set_eq:NN \vs \__scripture_poetry_mode_vertical_verse:n
1669 \cs_set_eq:NN \extraskip \__scripture_poetry_extra_skip:
1670 \cs_set_eq:NN \selah \__scripture_selah_output:
1671 \cs_set_protected_nopar:Npn \textright ##1
1672   {
1673     \__scripture_poetry_text_right:nn { \l__scripture_text_right_sep_tl } { ##1 }
1674   }
1675 \item
1676 \relax
1677 \cs_set_eq:NN \__scripture_tmp_para_end: \par
1678 \cs_set_eq:NN \par \__scripture_poetry_par:
1679 \hook_gput_next_code:nn { para / after }
1680   { \bool_gset_eq:NN \g__scripture_poetry_midparachap_show_verse_bool \l__scripture_midp
1681 }

(End definition for \__scripture_poetry_begin:.)
```

__scripture_poetry_end: End a poetry section in a scripture quotation.

```

1682 \cs_new_protected:Nn \__scripture_poetry_end:
1683 {
1684     \__scripture_calc_final_line_length:
1685     \skip_add:Nn \topsepadd \l__scripture_delta_below_skip
1686     \int_set_eq:NN \endparpenalty \lowpenalty
1687     \endlist
1688     \bool_gset_true:N \g__scripture_poetry_end_bool
1689     \hook_gput_next_code:nn { para / begin }
1690         { \bool_gset_false:N \g__scripture_poetry_end_bool }
1691 }

```

(End definition for `__scripture_poetry_end`.)

3.6 Public L^AT_EX Interface

`\scripturecurrentchapter` Globally stores the most recent argument of `\ch` and `\vs`. These could be used in hooks, for example.

```

1692 \cs_set_nopar:Npn \scripturecurrentchapter { }
1693 \cs_set_nopar:Npn \scripturecurrentverse { }

```

(End definition for `\scripturecurrentchapter` and `\scripturecurrentverse`. These functions are documented on page 6.)

`\scripturesetup` #1 : `<options>` to set.
Set key-value settings.

```

1694 \NewDocumentCommand { \scripturesetup } { m }
1695 {
1696     \keys_set:nn { scripture } { #1 }
1697 }

```

(End definition for `\scripturesetup`. This function is documented on page 6.)

`\textscripture` #1 : `<reference>` of quotation.
#2 : `<options>` to set.
#3 : `<quotation>` text.

Set an inline quotation. This is equivalent to calling the `scripture` environment with the `inline` option set.

```

1698 \NewDocumentCommand { \textscripture } { oo+m }
1699 {
1700     \tl_if_novalue:nTF { #2 }
1701     {
1702         \begin{scripture} [ #1 ] [ inline ]
1703     }
1704     {
1705         \begin{scripture} [ #1 ] [ inline, #2 ]
1706     }
1707     #3
1708     \end{scripture}
1709 }

```

(End definition for `\textscripture`. This function is documented on page 7.)

`scripture` #1 : `<reference>` of quotation.

```

#2 : <options> to set.
Format a scripture quotation with optional reference.
1710 \NewDocumentEnvironment { scripture } { oo }
1711   {
1712     \__scripture_begin:n { #2 }

#1 : <options> to set.
center 1713   \DeclareDocumentEnvironment { center } { o }
1714   {
1715     \__scripture_center_begin:n { ##1 }
1716     \ignorespaces
1717   }
1718   { \__scripture_center_end: }

#1 : <options> to set.
flushright 1719   \DeclareDocumentEnvironment { flushright } { o }
1720   {
1721     \__scripture_flushright_begin:n { ##1 }
1722     \ignorespaces
1723   }
1724   { \__scripture_flushright_end: }

#1 : <options> to set.
hanging 1725   \DeclareDocumentEnvironment { hanging } { o }
1726   {
1727     \__scripture_hanging_begin:n { ##1 }
1728     \ignorespaces
1729   }
1730   { \__scripture_hanging_end: }

midparachap 1731   \DeclareDocumentEnvironment { midparachap } { o }
1732   {
1733     \__scripture_mid_para_chap_begin:n { ##1 }
1734     \ignorespaces
1735   }
1736   { \__scripture_mid_para_chap_end: }

#1 : <options> to set.
narrow 1737   \DeclareDocumentEnvironment { narrow } { o }
1738   {
1739     \__scripture_narrow_begin:n { ##1 }
1740     \ignorespaces
1741   }
1742   { \__scripture_narrow_end: }

#1 : <options> to set.
poetry 1743   \DeclareDocumentEnvironment { poetryaux } { o }
1744   {
1745     \tl_if_novalue:nF { ##1 }
1746   }

```

```

1747     \keys_set:nn
1748         { scripture / poetry }
1749         { ##1 }
1750     }
1751     \__scripture_poetry_begin:
1752     \ignorespaces
1753   }
1754   { \__scripture_poetry_end: }
1755 \DeclareDocumentEnvironment { poetry } { }
1756   {
1757     \__scripture_obeylines:
1758     \poetryaux
1759   }
1760   { \endpoetryaux }

1761 \bool_if:NT \l__scripture_inline_bool
1762   {
1763     \tl_set:Nn \l__scripture_aboveskip_tl { Opt }
1764     \tl_set:Nn \l__scripture_beforeskip_tl { Opt }
1765     \tl_set:Nn \l__scripture_leftmargin_tl { Opt }
1766     \tl_set:Nn \l__scripture_rightmargin_tl { Opt }
1767   }
1768 \bool_if:NT \l__scripture_compact_bool
1769   {
1770     \scripturesetup { chapter / nodrop }
1771     \RenewDocumentEnvironment { center } { o } { \ignorespaces } { \unskip }
1772     \RenewDocumentEnvironment { flushright } { o } { \ignorespaces } { \unskip }
1773     \RenewDocumentEnvironment { hanging } { o } { \ignorespaces } { \unskip }
1774     \RenewDocumentEnvironment { midparachap } { o } { \ignorespaces } { \unskip }
1775     \RenewDocumentEnvironment { narrow } { o } { \ignorespaces } { \unskip }
1776     \RenewDocumentEnvironment { poetry } { o } { \ignorespaces } { \unskip }
1777     \cs_set_eq:NN \\ \unskip
1778     \cs_set_eq:NN \par \relax
1779     \cs_set_eq:NN \extraskip \relax
1780     \cs_set_eq:NN \nohang \relax
1781     \cs_set:Npn \selah
1782       {
1783         \group_begin:
1784         \l__scripture_selah_font_tl
1785         \c_space_tl
1786         \__scripture_selah_format:n { \l__scripture_selah_text_tl }
1787         \c_space_tl
1788         \group_end:
1789       }
1790     \cs_set_protected_nopar:Npn \textright ##1
1791       {
1792         \unskip
1793         \c_space_tl
1794         ##1
1795       }
1796     \mode_leave_vertical:
1797   }
1798 \peek_remove_spaces:n
1799   {

```

```

1800     \peek_meaning:NF \begin
1801         { \bool_gset_false:N \g__scripture_start_bool }
1802     }
1803     {
1804         \bool_if:NT \l__scripture_compact_bool
1805             { \cs_set_eq:NN \par \endgraf }
1806             \__scripture_end:n { #1 }
1807     }
1808 }
```

(End definition for `scripture` and others. These functions are documented on page 10.)

1809

Change History

v1.0	Add <code>language</code> option	16
	Add <code>name/font</code> option	16
	Add <code>name/format</code> option	16
	Add <code>redletter/colour</code> option . . .	17
	Add <code>redletter</code> option	16
	Add <code>reference/colour</code> option . . .	17
	Add <code>textright/sep</code> option	18
	Add <code>verse/colour</code> option	18
	Add divine name feature	4
	Add red letter feature	5
	Bug fixes	1
v1.1	General: Add <code>\scripturecurrentchapter</code> and	
	<code>\scripturecurrentverse</code>	
	variables	6
	Add <code>\selah</code> function	6
	Add <code>chapter/format</code> option	13
	Add <code>chapter/hide</code> option	13
	Add <code>chapter/showverse</code> option . .	14
	Add <code>chapter/show</code> option	14
	Add <code>compact</code> option	14
	Add <code>poetry/verse/left</code> option . .	22
	Add <code>poetry/verse/right</code> option . .	23
	Add <code>poetry/verse/sep</code> option . . .	23
	Add <code>verse/hide</code> option	19
	Add <code>verse/sep</code> option with small	
	default	19
	Add <code>verse/show</code> option	19
	Add before and after hooks for	
	verses and chapters	11
	Bug fixes	1
v1.2	General: Add <code>\textright</code> function . . .	6
	Add <code>chapter/colour</code> option	13
	Add <code>colour</code> option	14
	Add <code>language/variant</code> option . . .	16
v1.3	General: Add <code>\nofirstverse</code> function	5
	Add <code>\textscripture</code> function	7
	Add <code>added/font</code> option	12
	Add <code>added/format</code> option	12
	Add <code>inline/begin</code> option	15
	Add <code>inline/end</code> option	15
	Add <code>inline</code> option	15
	Add <code>reference/align</code> option	17
	Add <code>reference/newline</code> option . .	17
	Add <code>verse/firstformat</code> option . .	18
	Add <code>verse/firstsep</code> option	18
	Add <code>verse/first</code> option	18
	Add feature to highlight translator	
	added words	4
	Bug fixes	1
	Remove <code>reference/delim</code> option .	12

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols	
\,	87, 90 ₆₅

\`	8, 1777	\box_ht_plus_dp:N	1246
\^	1596, 1599	\box_move_down:nn	551, 1019, 1409
A		\box_new:N	330,
\abovedisplayshortskip	627, 628	446, 447, 1140, 1143, 1145, 1146, 1147	
\abovedisplayskip	628	\box_set_dp:Nn	562, 1030, 1420
aboveskip (option)	7, 12, 38, 43, 43, 45, 48, 53	\box_set_ht:Nn	561, 1029, 1419
\added	4, 12, 13, 706	\box_set_to_last:N	1154, 1219
added/font (option)	4, 12, 65	\box_use:N	374, 510, 556, 1024, 1033, 1414, 1498
added/format (option)	4, 13, 65	\box_use_drop:N	1237, 1242, 1257, 1259, 1263
\addvspace	295, 299, 677, 740,	\box_wd:N	357, 369, 481, 1165, 1227
	843, 849, 892, 949, 1098, 1319, 1643	\break	308
B		C	
\baselineskip	31, 293,	center (environment)	8, 63
	295, 360, 362, 461, 552, 627, 650,	center/aboveskip (option)	20
	673, 892, 949, 1020, 1098, 1248,	center/belowskip (option)	20
	1253, 1269, 1319, 1349, 1410, 1643	center/leftmargin (option)	20
\begin	1702, 1705, 1800	center/rightmargin (option)	20
\belowdisplayshortskip	629	\centering	900
\belowdisplayskip	630	\ch	3, 4, 6,
belowskip (option)	7, 13, 41, 43		13, 14, 21, 29, 54, 62, 679, 1111, 1658
\bfseries	12, 13, 17, 41, 135	\ch*	3, 4
bool commands:		chap/font (option)	11
\bool_gset_eq:NN	1356, 1680	chap/sep (option)	11
\bool_gset_false:N	397, 700, 878, 935, 1084,	chapter/color (option)	13, 13
	1305, 1350, 1629, 1657, 1690, 1801	chapter/colour (option)	13, 13, 65
\bool_gset_true:N	381, 699, 1688	chapter/drop (option)	13, 13
\bool_if:NTF	354, 379, 394, 513,	chapter/font (option)	13
	523, 534, 563, 591, 598, 658, 681,	chapter/format (option)	13, 65
	683, 766, 779, 792, 856, 873, 913,	chapter/hide (option)	13, 14, 65
	930, 1036, 1062, 1079, 1113, 1115,	chapter/nodrop (option)	13, 13, 14
	1187, 1283, 1300, 1513, 1546, 1613,	chapter/sep (option)	14
	1624, 1660, 1662, 1761, 1768, 1805	chapter/show (option)	13, 14, 65
\bool_if:nTF	686	chapter/showverse (option)	14, 14, 21, 21, 65
\bool_if_p:n	1203, 1204, 1502, 1503, 1528, 1529	char commands:	
	604	\char_set_catcode_active:N	1596, 1599
\bool_lazy_all:nTF	1202	\clubpenalty	482, 483, 491
\bool_lazy_and:nnTF	770	color (option)	14, 14
\bool_lazy_any:nTF	303,	color commands:	
\bool_lazy_or:nnTF	749, 786, 810, 824, 829, 1501, 1527	\color_group_begin:	1137
	1206, 1206, 1210, 1287, 1617	\color_select:n	336, 382,
\bool_new:N	284, 285,		387, 396, 402, 477, 528, 603, 747, 1521
	376, 580, 581, 655, 1139, 1341, 1342	\color_set:nn	744
\bool_not_p:n	608	colour (option)	14, 14, 65
\bool_set_false:N	586, 590, 593, 594, 1207	compact (option)	7, 14, 15, 65
	587, 662, 722,	cs commands:	
\bool_set_true:N	860, 917, 1066, 1206, 1210, 1287, 1617	\cs_gset_nopar:Nn	637
box commands:		\cs_gset_nopar:Npn	.. 455, 456, 520, 521, 584, 1510, 1511
\box_clear:N	1228	\cs_gset_protected_nopar:Nn	.. 1597
\box_ht:N	459		

\cs_new_protected:Nn	287, 301, 331, 348, 377, 392, 407, 453, 494, 518, 546, 582, 625, 656, 782, 854, 904, 911, 963, 971, 1043, 1060, 1126, 1148, 1193, 1214, 1281, 1333, 1347, 1362, 1377, 1386, 1508, 1541, 1565, 1574, 1603, 1611, 1682	99, 146, 206, 209, 218, 221, 236, 271, 561, 562, 632, 648, 1029, 1030, 1419, 1420
\cs_new_protected:Npn	1133	dropchap (option) 3
\cs_new_protected_nopar:Nn	1055	
\cs_set:Npn	1781	
\cs_set_eq:NN	702, 703, 704, 705, 1121, 1122, 1578, 1582, 1600, 1668, 1669, 1670, 1677, 1678, 1777, 1778, 1779, 1780, 1806	
\cs_set_nopar:Npn	1692, 1693	
\cs_set_protected_nopar:Npn	706, 713, 720, 724, 728, 732, 1671, 1790	
D		
\DeclareDocumentCommand	679, 1111, 1658	
\DeclareDocumentEnvironment	1713, 1719, 1725, 1731, 1737, 1743, 1755	
dim commands:		
\dim_add:Nn	758, 762, 763, 814, 836	
\dim_compare:nNnTF	292, 356, 368, 632, 644, 648, 840, 974, 1163, 1245, 1396, 1435, 1444, 1471	
\dim_compare:nTF	881, 938, 1087, 1308, 1632	
\dim_compare_p:n	750, 751, 811, 812, 830, 831	
\dim_eval:n	498, 500, 502, 504, 673, 979, 984, 989, 994, 999, 1010, 1427, 1429, 1431, 1433, 1457, 1459, 1461, 1463, 1484, 1486, 1488, 1490, 1589, 1591	
\dim_gadd:Nn	1235	
\dim_gset:Nn	634, 1227	
\dim_gset_eq:NN	646, 1218	
\dim_new:N	448, 449, 450, 452, 624, 970, 1141, 1343, 1344, 1345	
\dim_ratio:nn	465	
\dim_set:Nn	458, 460, 462, 480, 639, 1101, 1104, 1105, 1401, 1421, 1450, 1477	
\dim_set_eq:NN	701, 952, 953, 1103, 1109, 1267, 1322, 1323, 1324, 1325, 1391, 1395, 1646, 1647, 1648, 1649, 1655, 1656	
\dim_sub:Nn	753, 818	
\dim_use:N	639	
\dim_zero:N	897, 898, 956, 957, 1081, 1108, 1328, 1394, 1448, 1475, 1652	
E		
\emph	13, 28	
\end	1605, 1708	
\endgraf	1806	
\endlist	909, 968, 1131, 1338, 1687	
\endpoetryaux	1760	
environments:		
center	8, 63	
flushright	8, 63	
hanging	8, 63	
midparachap	9, 63	
narrow	9, 63	
poetry	10, 63	
scripture	10, 62	
\everydisplay	39, 696	
exp commands:		
\exp_args:NnV	744	
\exp_args:NV	336, 382, 387, 477, 528, 603, 1521	
extraskip (option)	4, 15	
\extraskip	4, 14, 15, 21, 573, 702, 1669, 1779	
F		
\finalhyphendemerits	325, 1374	
flushright (environment)	8, 63	
flushright/aboveskip (option)	20	
flushright/belowskip (option)	20	
flushright/leftmargin (option)	20	
flushright/rightmargin (option)	20	
font (option)	15	
\fontsize	472	
G		
\glueexpr	293, 841, 882, 939, 1088, 1309, 1633	
\GOD	5, 728	
\goodbreak	1258	
group commands:		
\group_begin:	333, 508, 522, 526, 596, 600, 708, 715, 1031, 1179, 1379, 1496, 1512, 1518, 1543, 1567, 1595, 1783	
\c_group_begin_token	1136	
\group_end:	346, 512, 531, 544, 612, 617, 622, 711, 718, 1035, 1185, 1384, 1500, 1523, 1539, 1563, 1572, 1602, 1788	
H		
hanging (environment)	8, 63	
hanging/aboveskip (option)	20	

hanging/belowskip (option)	20
hanging/hang (option)	5, 5, 20
hanging/leftmargin (option)	21
hanging/rightmargin (option)	21
hbox commands:	
\hbox:n	320, 1369
\hbox_overlap_left:n	554, 1022, 1048, 1412, 1515, 1548, 1554
\hbox_overlap_right:n	1556
\hbox_set:Nn	350, 457, 469, 549, 1017, 1155, 1220, 1407
\hbox_to_wd:nn	1058
\hbox_unpack:N	1222
\hbox_unpack_drop:N	1157, 1173, 1182
\hfil	317, 1366
\hfill	310, 322, 364, 1371
hook commands:	
\hook_gclear_next_code:n	736, 1467
\hook_gput_next_code:nn	385, 400, 484, 490, 569, 688, 768, 1040, 1273, 1352, 1354, 1440, 1465, 1469, 1679, 1689
\hook_new:n	1340
\hook_new_pair:nn	282, 283
\hook_use:n	509, 511, 525, 533, 540, 541, 597, 621, 1032, 1034, 1497, 1499, 1517, 1525, 1535, 1536, 1593
hooks:	
scripture/chap/after	11, 11, 11, 13, 29
scripture/chap/before	11, 11, 13, 29
scripture/poetry/para/after	54
scripture/verse/after	11, 19, 29
scripture/verse/before	11, 11, 19, 29
I	
\iflanguageloaded	418
\ignorespaces	1716, 1722, 1728, 1734, 1740, 1752, 1771, 1772, 1773, 1774, 1775, 1776
indent (option)	16, 16
inline (option)	7, 15, 15, 15, 15, 62, 65
inline/begin (option)	7, 15, 15, 65
inline/end (option)	7, 15, 15, 65
int commands:	
\int_compare:nNnTF	289, 361, 487, 571, 575, 755, 815, 833, 891, 948, 1097, 1230, 1276, 1318, 1442, 1642
\int_gset_eq:NN	486, 1217, 1272
\int_gzero:N	297, 574, 689, 893, 950, 1099, 1275, 1320, 1644
\int_new:N	286, 451, 1142, 1144, 1346
\int_set:Nn	640, 697, 1250, 1608
\int_set_eq:NN	482, 491, 698, 807, 908, 967, 1130, 1151, 1174, 1337, 1584, 1686
\int_use:N	640, 1608
\int_zero:N	325, 806, 1268, 1374
\c_zero_int	361, 576, 756, 816, 834, 1277
\item	39, 901, 960, 1123, 1330, 1675
\itemindent	1104, 1325, 1648
\itshape	17, 152
K	
\kern	613, 618
keys commands:	
\l_keys_choice_tl	125
\keys_define:nn	18
\keys_set:nn	666, 864, 921, 1070, 1198, 1291, 1696, 1747
L	
\labelsep	898, 957, 1108, 1328, 1652
language (option)	16, 16, 24, 65
language/variant (option)	16, 65
leftmargin (option)	16
\leftmargin	897, 952, 956, 975, 979, 986, 991, 996, 1001, 1101, 1322, 1646
\leftskip	40, 762, 1170, 1181
legacy commands:	
\legacy_if:nTF	585, 669
\linewidth	17, 139, 359, 371, 501, 505, 507, 577, 644, 646, 753, 759, 814, 819, 822, 836, 837, 991, 1001, 1004, 1041, 1170, 1278, 1430, 1434, 1460, 1464, 1487, 1491, 1588, 1592
\list	870, 927, 1076, 1297, 1621
\listparindent	1105, 1324, 1569, 1571, 1649, 1655
\Lord	5, 724
M	
\medskipamount	15, 20, 22, 67, 200, 203, 212, 215, 224, 227, 244, 247, 256, 259
midparachap (environment)	9, 63
midparachap/hideverse (option)	14, 14, 21, 21
midparachap/showverse (option)	14, 21, 21
mode commands:	
\mode_if_horizontal:TF	868, 925, 1074, 1295, 1619
\mode_if_inner:TF	1239
\mode_if_vertical:TF	588, 675, 738, 799, 1006, 1045, 1389, 1576
\mode_leave_vertical:	367, 589, 1392, 1796

msg commands:

\msg_error:nn	660, 858, 915, 1064, 1285, 1615
\msg_error:nnn	431
\msg_new:nnnn	6, 10, 14
\msg_warning:nnn	438

N

\name	5, 16, 713, 726, 730
name/font (option)	5, 16, 65
name/format (option)	5, 16, 65
narrow (environment)	9, 63
narrow/aboveskip (option)	22
narrow/belowskip (option)	22
narrow/leftmargin (option)	22
narrow/rightmargin (option)	22
\NeedsTeXFormat	3
\NewDocumentCommand	1694, 1698
\NewDocumentEnvironment	1710
\nobreak	321, 1370
\nofirstverse	5, 65, 720
\nohang	5, 1122, 1780
noindent (option)	16, 16
\noindent	496, 1180, 1233, 1241, 1256, 1262, 1270, 1579
\nointerlineskip	1162, 1229
\noversefirst	18

O

\obeylines	3
options:		
aboveskip	..	7, 12, 38, 43, 43, 45, 48, 53
added/font	4, 12, 65
added/format	4, 13, 65
belowskip	7, 13, 41, 43
center/aboveskip	20
center/belowskip	20
center/leftmargin	20
center/rightmargin	20
chap/font	11
chap/sep	11
chapter/color	13, 13
chapter/colour	13, 13, 65
chapter/drop	13, 13
chapter/font	13
chapter/format	13, 65
chapter/hide	13, 14, 65
chapter/nodrop	13, 13, 14
chapter/sep	14
chapter/show	13, 14, 65
chapter/showverse	..	14, 14, 21, 21, 65
color	14, 14
colour	14, 14, 65
compact	7, 14, 15, 65

dropchap	3
extraskip	4, 15
flushright/aboveskip	20
flushright/belowskip	20
flushright/leftmargin	20
flushright/rightmargin	20
font	15
hanging/aboveskip	20
hanging/belowskip	20
hanging/hang	5, 5, 20
hanging/leftmargin	21
hanging/rightmargin	21
indent	16, 16
inline	7, 15, 15, 15, 15, 62, 65
inline/begin	7, 15, 15, 65
inline/end	7, 15, 15, 65
language	16, 16, 24, 65
language/variant	16, 65
leftmargin	16
midparachap/hideverse	..	14, 14, 21, 21
midparachap/showverse	..	14, 21, 21
name/font	5, 16, 65
name/format	5, 16, 65
narrow/aboveskip	22
narrow/belowskip	22
narrow/leftmargin	22
narrow/rightmargin	22
noindent	16, 16
parindent	5, 16, 16, 16
parskip	16, 38
poetry/aboveskip	22
poetry/belowskip	22
poetry/bigindent	22
poetry/indent	22
poetry/leftmargin	22
poetry/rightmargin	22
poetry/verse/left	22, 23, 65
poetry/verse/right	22, 23, 65
poetry/verse/sep	23, 65
redletter	6, 17, 17, 65
redletter/color	17, 17
redletter/colour	6, 17, 17, 65
reference/align	7, 15, 17, 65
reference/color	17, 17
reference/colour	17, 17, 65
reference/delim	65
reference/font	17
reference/format	7, 15, 17
reference/newline	17, 65
reference/sep	7, 15, 17, 17
rightmargin	17
selah/font	6, 17
selah/format	6, 17
selah/sep	6, 18

selah/text	6, 17, 18
textright/sep	7, 18, 65
verse/color	18, 18
verse/colour	18, 18, 65
verse/first	5, 18, 18, 65
verse/firstformat	5, 18, 18, 65
verse/firstsep	18, 18, 65
verse/font	11, 19
verse/format	19
verse/hide	19, 19, 65
verse/sep	11, 19, 65
verse/show	19, 19, 65
version	19
version/delim	19
version/format	7, 15, 19
P	
\pagegoal	1248, 1253
\pagetotal	1248, 1253
\par	7, 14, 15, 566, 672, 828, 869, 926, 1075, 1153, 1184, 1209, 1216, 1266, 1296, 1607, 1620, 1677, 1678, 1778, 1806
para commands:	
\para_end:	312, 326
\para_omit_indent:	776
\para_raw_noindent:	1057
\parfillskip	324, 1183, 1373
parindent (option)	5, 16, 16, 16
\parindent	16, 45, 47, 110, 701, 1109, 1324, 1325, 1656
\parsep	895, 954, 1106, 1326, 1650
\parshape	2, 40, 42, 54, 56, 57, 497, 577, 759, 819, 822, 837, 983, 1041, 1278, 1426, 1456, 1483, 1586
\parskip (option)	16, 38
\parskip	16, 31, 38, 113, 293, 355, 650, 673, 737, 742, 841, 845, 876, 877, 882, 895, 933, 934, 939, 954, 1082, 1083, 1088, 1106, 1212, 1269, 1303, 1304, 1309, 1326, 1349, 1627, 1628, 1633
\partopsep	896, 955, 1107, 1327, 1651
peek commands:	
\peek_meaning:NTF	1605, 1800
\peek_remove_spaces:n	1798
\penalty	318, 489, 1367
poetry (environment)	10, 63
poetry/aboveskip (option)	22
poetry/belowskip (option)	22
poetry/bigindent (option)	22
poetry/indent (option)	22
poetry/leftmargin (option)	22
poetry/rightmargin (option)	22
poetry/verse/left (option)	22, 23, 65
poetry/verse/right (option)	22, 23, 65
poetry/verse/sep (option)	23, 65
\poetryaux	1758
\postdisplaypenalty	698, 806, 807
\predisplaypenalty	697
\predisplaysize	632, 635, 639
\prevdepth	49, 1218, 1267
\prevgraf	49, 361, 486, 640, 1217, 1231, 1268, 1584, 1608
\ProcessKeyOptions	281
\ProvidesExplPackage	4
R	
\raggedleft	959
\raggedright	1654
redletter (option)	6, 17, 17, 65
redletter/color (option)	17, 17
redletter/colour (option)	6, 17, 17, 65
\redletteroff	6, 17, 704
\redletteron	6, 17, 703
reference/align (option)	7, 15, 17, 65
reference/color (option)	17, 17
reference/colour (option)	17, 17, 65
reference/delim (option)	65
reference/font (option)	17
reference/format (option)	7, 15, 17
reference/newline (option)	17, 65
reference/sep (option)	7, 15, 17, 17
\relax	7, 14, 15, 902, 961, 1124, 1331, 1676, 1778, 1779, 1780
\renewcommand*	6
\RenewDocumentEnvironment	
...	1771, 1772, 1773, 1774, 1775, 1776
rightmargin (option)	17
\rightmargin	953, 1103, 1323, 1647
\rightskip	40, 763, 1170
S	
scripture (environment)	10, 62
scripture internal commands:	
\l_scripture_aboveskip_tl	20, 677, 1763
\l_scripture_active_bool	284, 658, 662
\l_scripture_active_inner_bool	284, 856, 860, 913, 917, 1062, 1066, 1283, 1287, 1613, 1617
\l_scripture_added_font_tl	23, 709
__scripture_added_format:n	26, 710
__scripture_begin:n	656, 656, 1712
\l_scripture_belowskip_tl	29, 841, 845, 849, 1764

```

\__scripture_calc_final_line_-
    length: ..... 625,
    625, 808, 906, 965, 1128, 1335, 1684
\l__scripture_center_aboveskip_-
    tl ..... 198, 882, 888, 889
\__scripture_center_begin:n .....
    ..... 854, 854, 1715
\l__scripture_center_bellowskip_-
    tl ..... 201, 872
\__scripture_center_end: .....
    ..... 904, 904, 1718
\l__scripture_center_leftmargin_-
    tl ..... 204
\l__scripture_center_rightmargin_-
    tl ..... 207
\__scripture_chap:n ... 546, 546, 685
\l__scripture_chap_box .....
    446, 510, 549, 561, 562, 1017, 1029,
    1030, 1033, 1407, 1419, 1420, 1498
\l__scripture_chap_drop_bool ...
    ..... 46, 54, 683, 1115, 1204, 1662
\l__scripture_chap_font_tl .....
    ..... 39, 471, 529, 1519
\l__scripture_chap_fontsize_dim .
    ..... 448, 462, 473, 474
\__scripture_chap_format:n .....
    ..... 49, 478, 530, 1522
\l__scripture_chap_height_dim ...
    ..... 449, 460, 466
\g__scripture_chap_par_prevgraf_-
    int ..... 290,
    297, 451, 486, 488, 572, 574, 689,
    891, 893, 948, 950, 1097, 1099,
    1272, 1275, 1318, 1320, 1642, 1644
\l__scripture_chap_sep_tl .....
    ..... 56, 499, 501, 503, 505, 532,
    557, 977, 987, 992, 997, 1002, 1008,
    1012, 1025, 1167, 1234, 1235, 1395,
    1397, 1445, 1452, 1472, 1479, 1524
\l__scripture_chap_show_bool ...
    ... 52, 59, 523, 681, 1113, 1513, 1660
\l__scripture_chap_show_verse_-
    bool ..... 62,
    513, 534, 1036, 1203, 1207, 1502, 1528
\l__scripture_chap_tmp_box . 447,
    457, 459, 469, 481, 556, 1024, 1414
\l__scripture_chap_tmp_box .... 446
\l__scripture_chap_width_dim ...
    ..... 450, 480, 499, 501,
    503, 505, 975, 979, 986, 991, 996,
    1001, 1166, 1234, 1235, 1397, 1404,
    1423, 1436, 1445, 1452, 1472, 1479
\l__scripture_chap_X_height_dim .
    ..... 452, 458, 461, 467
\l__scripture_chapter_colour_tl .
    ... 42, 476, 477, 527, 528, 1520, 1521
\l__scripture_clubpenalty_saved_-
    int ..... 286, 482, 491
\l__scripture_colour_tl . 32, 744, 745
\l__scripture_compact_bool .....
    ..... 36, 1768, 1805
\l__scripture_currenvir_str .....
    ..... 304, 305, 383, 385,
    398, 400, 608, 653, 663, 772, 773,
    774, 861, 918, 1067, 1195, 1288, 1618
\l__scripture_delta_below_skip ..
    ..... 853,
    872, 877, 885, 889, 907, 929, 934,
    942, 946, 966, 1078, 1083, 1091,
    1095, 1129, 1299, 1304, 1312, 1316,
    1336, 1623, 1628, 1636, 1640, 1685
\__scripture_drop_chap_output: ...
    ..... 494, 494, 567, 1172, 1186
\__scripture_drop_chap_set_up:n .
    ..... 453, 453, 548, 973, 1388
\__scripture_end:n ... 782, 782, 1807
\__scripture_extra_skip: 287, 287, 702
\l__scripture_extraskip_tl .....
    ..... 65, 293, 299, 1349
\g__scripture_final_line_dim ...
    ..... 357, 369, 372, 624,
    634, 644, 646, 648, 1227, 1235, 1271
\l__scripture_flushright_-
    aboveskip_tl ... 210, 939, 945, 946
\__scripture_flushright_begin:n .
    ..... 911, 911, 1721
\l__scripture_flushright_-
    belowskip_tl ..... 213, 929
\__scripture_flushright_end: ...
    ..... 963, 963, 1724
\l__scripture_flushright_-
    leftmargin_tl ..... 216, 952
\l__scripture_flushright_-
    rightmargin_tl ..... 219, 953
\l__scripture_font_tl ..... 68, 743
\__scripture_format_full_ref:n ..
    ..... 331, 331, 352, 795
\l__scripture_hanging_aboveskip_-
    tl ..... 222, 1088, 1094, 1095
\__scripture_hanging_begin:n ...
    ..... 1060, 1060, 1727
\l__scripture_hanging_bellowskip_-
    tl ..... 225, 1078
\__scripture_hanging_chap:n .....
    ..... 971, 971, 1116
\__scripture_hanging_end: .....
    ..... 1126, 1126, 1730

```

```

\l__scripture_hanging_hang_tl . . .
    ..... 228, 1102, 1104, 1105
\l__scripture_hanging_leftmargin_-
    tl ..... 231, 1102
\l__scripture_hanging_parindent_-
    saved_dim ... 970, 1012, 1058, 1109
\l__scripture_hanging_rightmargin_-
    tl ..... 234, 1103
\l__scripture_hanging_verse:n . . .
    ..... 1043, 1043, 1121
\l__scripture_indent_bool 71, 106, 766
\l__scripture_inline_begin_t1 85, 780
\l__scripture_inline_bool . . .
    ..... 74, 779, 792, 1761
\l__scripture_inline_end_t1 . 88, 793
\l__scripture_language_t1 . . .
    .. 91, 409, 413, 418, 422, 427, 434, 441
\l__scripture_language_variant_-
    tl ..... 94, 420, 426
\l__scripture_leftmargin_t1 . . .
    ..... 97, 750,
    754, 758, 762, 811, 814, 818, 830, 1765
\l__scripture_mid_para_chap_-
    begin:n ..... 1193, 1193, 1733
\l__scripture_mid_para_chap_bool
    ..... 563, 1139, 1210
\l__scripture_mid_para_chap_box . . .
    ..... 1145,
    1211, 1242, 1246, 1252, 1259, 1263
\l__scripture_mid_para_chap_end: . . .
    ..... 1214, 1214, 1736
\l__scripture_mid_para_chap_-
    line_box . . .
    .. 1140, 1154, 1157, 1219, 1222, 1237
\g__scripture_mid_para_chap_-
    prevdepth_dim ... 1141, 1218, 1267
\g__scripture_mid_para_chap_-
    prevgraf_int ... 1142, 1217, 1272
\l__scripture_mid_para_chap_-
    snap_box . . .
    .. 1143, 1155,
    1165, 1173, 1182, 1220, 1227, 1228
\l__scripture_mid_para_chap_-
    spacefactor_int . 1144, 1151, 1174
\l__scripture_mid_para_chap_-
    split_box ..... 1145, 1252, 1255
\l__scripture_mid_para_chap_-
    split_top_box ... 1145, 1254, 1257
\l__scripture_mid_para_drop_chap_-
    output: ..... 564, 1148, 1148
\l__scripture_midparachap_show_-
    verse_bool . . .
    .. 237, 239, 1187, 1206, 1358, 1680
\l__scripture_name_font_t1 . 100, 716
\l__scripture_name_format:n . 103, 717
\l__scripture_narrow_aboveskip_-
    tl ..... 242, 1309, 1315, 1316
\l__scripture_narrow_begin:n . . .
    ..... 1281, 1281, 1739
\l__scripture_narrow_belowskip_-
    tl ..... 245, 1299
\l__scripture_narrow_end: . . .
    ..... 1333, 1333, 1742
\l__scripture_narrow_leftmargin_-
    tl ..... 248, 1322
\l__scripture_narrow_rightmargin_-
    tl ..... 251, 1323
\l__scripture_no_verse_first_-
    bool ..... 581, 591, 594, 722
\l__scripture_nodrop_chap:n . . .
    ..... 518, 518, 692, 694, 1117, 1119
\l__scripture_nohang: . . .
    ..... 1015, 1055, 1055, 1122
\l__scripture_obeylines: . . .
    ..... 31, 56, 63, 1595, 1597, 1757
\l__scripture_obeylines_end: . . .
    ..... 1600, 1603
\l__scripture_parindent_t1 . 108, 701
\l__scripture_parskip_correction_-
    skip ..... 654, 737, 740
\l__scripture_parskip_t1 111, 737, 742
\l__scripture_poetry_aboveskip_-
    tl ..... 254, 1633, 1639, 1640
\l__scripture_poetry_begin: . . .
    ..... 1611, 1611, 1751
\l__scripture_poetry_belowskip_-
    tl ..... 257, 1623
\l__scripture_poetry_big_indent_-
    tl ..... 260, 1432, 1434,
    1462, 1464, 1489, 1491, 1590, 1592
\l__scripture_poetry_chap:n . . .
    ..... 1386, 1386, 1663
\l__scripture_poetry_chap_-
    indent_dim . . .
    .. 1343, 1391, 1394, 1399, 1403, 1424
\l__scripture_poetry_chap_-
    parshape_correction_dim 1345,
    1421, 1428, 1430, 1448, 1450,
    1458, 1460, 1475, 1477, 1485, 1487
\l__scripture_poetry_chap_sep_-
    dim 1343, 1395, 1401, 1415, 1423, 1436
\l__scripture_poetry_end: . . .
    ..... 1682, 1682, 1754
\g__scripture_poetry_end_bool . . .
    .. 354, 700, 1341, 1688, 1690
\l__scripture_poetry_extra_skip: . . .
    ..... 1347, 1347, 1669

```


\scripturecurrentchapter	6, 29, 65, 455, 520, 1510, 1692
\scripturecurrentverse	6, 29, 65, 456, 521, 584, 1511, 1692
\scripturesetup	6, 12, 19–22, 1694, 1770
\scshape	16, 102
\selah	6, 17, 18, 65, 1670, 1781
selah/font (option)	6, 17
selah/format (option)	6, 17
selah/sep (option)	6, 18
selah/text (option)	6, 17, 18
\selectfont	475
\selectlanguage	16, 413, 422, 425
skip commands:	
\skip_add:Nn	877, 907, 934, 966, 1083, 1129, 1304, 1336, 1628, 1685
\skip_eval:n	845
\skip_horizontal:N	532, 557, 794, 1025, 1271, 1415, 1524, 1560, 1571
\skip_horizontal:n	319, 372, 1181, 1234, 1368, 1569
\skip_new:N	654, 853
\skip_set:Nn	627, 737
\skip_set_eq:NN	628, 742, 872, 888, 895, 929, 945, 954, 1078, 1094, 1106, 1299, 1315, 1326, 1623, 1639
\skip_sub:Nn	876, 889, 933, 946, 1082, 1095, 1303, 1316, 1627, 1640
\skip_vertical:N	360
\skip_vertical:n	355, 362, 650, 1269, 1349
\skip_zero:N	324, 629, 630, 875, 884, 885, 896, 932, 941, 942, 955, 1090, 1091, 1107, 1183, 1212, 1302, 1311, 1312, 1327, 1373, 1626, 1635, 1636, 1650, 1651
\c_zero_skip	22, 31, 882, 939, 1088, 1309, 1633
\spacefactor	1151, 1174
str commands:	
\str_if_eq:nnTF	335, 383, 398, 476, 527, 602, 745, 1520
\str_if_eq_p:nn	304, 305, 608, 772, 773, 774
\str_new:N	653
\strut	309, 671, 1047, 1152, 1351, 1545
T	
TeX and L ^A T _E X 2 _{ε} commands:	
\@endparpenalty	908, 967, 1130, 1337, 1686
\@highpenalty	807
\@ifpackageloaded	411, 416
\@listdepth	576, 756, 816, 834, 1277
U	
\unpenalty	1160, 1225
\unskip	41, 307, 316, 790, 801, 802, 1150, 1158, 1159, 1223, 1224, 1365, 1771, 1772, 1773, 1774, 1775, 1776, 1777, 1792
\usepackage	12
V	
\vbadness	1250
vbox commands:	
\vbox_set_end:	1238
\vbox_set_split_to_ht:NNn	1251
\vbox_set_top:Nn	1254
\vbox_set_top:Nw	49
\vbox_unpack_drop:N	1255
verse/color (option)	18, 18
verse/colour (option)	18, 18, 65
verse/first (option)	5, 18, 18, 18, 65

<code>verse/firstformat</code> (option) . . .	<i>5, 18, 18, 65</i>	<code>version</code> (option)	<i>19</i>
<code>verse/firstsep</code> (option)	<i>18, 18, 65</i>	<code>version/delim</code> (option)	<i>19</i>
<code>verse/font</code> (option)	<i>11, 19</i>	<code>version/format</code> (option)	<i>7, 15, 19</i>
<code>verse/format</code> (option)	<i>19</i>	<code>\vs</code>	<i>5–7, 14, 18, 19, 21, 23, 47, 62,</i>
<code>verse/hide</code> (option)	<i>19, 19, 65</i>		<i>542, 705, 1121, 1537, 1578, 1582, 1668</i>
<code>verse/sep</code> (option)	<i>11, 19, 65</i>	<code>\vspace</code>	<i>673</i>
<code>verse/show</code> (option)	<i>19, 19, 65</i>		